

Dimensional stability of composites from plastics and cornstalk fibers

Poo Chow

Tait C. Bowers

Dilpreet S. Bajwa

John A. Youngquist

James H. Muehl

Nicole M. Stark

Andrzej M. Krzysik

Li Quang

Abstract

Thermoplastic composites using corn crop residues were developed and their dimensional stability was evaluated in this study. The fibers were obtained from cornstalks or cornstems collected from farms in Central Illinois. They were blended with both virgin and recycled high-density poly-

ethylene (HDPE) to make 1/2-inch-thick composite panels; and both virgin and recycled polypropylene to produce 1/4-inch-thick composite panels. The 1/2-inch-thick melt-blended composite panels were made using 60 percent low-density polyethylene (LDPE) compounded with 40

Chow:

Professor, Dept. of Natural Resources and Environmental Sciences, Univ. of Illinois, Urbana, Illinois

Bowers, Bajwa:

Graduate Students, Dept. of Natural Resources and Environmental Sciences, Univ. of Illinois, Urbana, Illinois

Youngquist:

Project Leader, USDA Forest Serv., Forest Prod. Lab., Madison, Wisconsin

Muehl:

Forest Products Technologist, USDA Forest Serv., Forest Prod. Lab., Madison, Wisconsin

Stark:

Chemical Engineer, USDA Forest Serv., Forest Prod. Lab., Madison, Wisconsin

Krzysik:

Visiting Senior Scientist, USDA Forest Serv., Forest Prod. Lab., Madison, Wisconsin

Quang:

USDA Forest Serv., Forest Prod. Lab., Madison, Wisconsin

percent cornstalk fibers at two density levels. They were blended in a corotating, intermeshing segmented twin-screw extruder with a length-to-diameter ratio of 32:1. The cooled strands were pelletized. The compounded pellets were placed in a mold and compressed into panels using 1/2-inch stops.

Steam-pressurized cornstalk fibers (10% and 20% levels) were blended with both virgin HDPE and recycled HDPE (90% and 80% levels) for the production of resin blending-HDPE panels. The well-mixed material was then formed into a mat in a deckle box that had been placed on a caul plate. The mats were pressed in the steam-heated platen press to 1/2-inch-thick experimental composite panels. Water absorption and thickness swell properties (after a 24-hour water soak and 2-hour water-boil), and linear expansion of all panels exposed from 50 to 90 percent relative humidity were determined according to ASTM D 1037 standards. The ASTM D 955 standard was used to measure the dimensional shrinkage from mold dimensions of molded cornstalk-polypropylene composite samples in the shape of the standard ASTM injection-molded specimen obtained from a 33-ton Cincinnati Milacron injection-molder. The results showed that most of the cornstalk-polypropylene composite specimens obtained an

average thickness shrinkage of about 5 percent. Width shrinkage was no more than 1.5 percent. Length shrinkage averaged about 0.5 percent. In terms of water resistance, the melt-blended LDPE panels were superior to the melt-blended HDPE and polypropylene panels. It was found that the composite made with 10 percent recycled polypropylene and 90 percent cornstalks was the least water resistant. The polypropylene composite panel obtained overall lower average water absorption, thickness swell, and linear expansion values than those of the HDPE composite panels in three tests (24-hour water-soak, 2-hour water-boil, and the 90% high humidity exposure tests). All resin-blended composite panels exhibited relatively low water resistance and dimensional stability in both 24-hour water-soak and 2-hour water-boil tests. The 10 percent virgin HDPE composite panels did not survive the 2-hour water-boil test. The 20 percent HDPE and polypropylene composite panels did show the slightly lower values in thickness swell in the water soaking test. The thermal expansion of the melt-blended cornstalk-LDPE composite panels appeared to be a problem in determining the cause (whether or not it was due to heat or moisture) of the dimensional expansion in the 2-hour water-boil evaluation.

Fifth International Conference on Woodfiber-Plastic Composites

May 26-27, 1999

The Madison Concourse Hotel

Madison, Wisconsin

Sponsored by the USDA Forest Service in cooperation with the American Plastics Council, the University of Wisconsin, the University of Toronto, the Cellulose, Paper, and Textile Division of the American Chemical Society, and the Forest Products Society.



Forest Products Society
2801 Marshall Court
Madison, WI 53705-2295
phone: 608-231-1361
fax: 608-231-2152
www.forestprod.org