

Metric and Other Physical Conversion Factors

The *State Energy Price and Expenditure data* and other Energy Information Administration publications are expressed predominately in units that historically have been used in the United States, such as British thermal units, barrels, cubic feet, and short tons. However, because U.S. commerce involves other nations, most of which use metric units of measure, the U.S. Government is committed to the transition to the metric system, as stated in the Metric Conversion Act of 1975 (Public Law 94-168), amended by the Omnibus Trade and Competitiveness Act of 1988 (Public Law 100-418), and Executive Order 12770 of July 25, 1991.

The metric conversion factors presented in Table A1 can be used to calculate the metric-unit equivalents of values expressed in U.S. customary units. For example, 500 short tons are the equivalent of 453.6 metric

tons (500 short tons x 0.9071847 metric tons/short ton = 453.6 metric tons).

In the metric system of weights and measures, the names of multiples and subdivisions of any unit may be derived by combining the name of the unit with prefixes, such as deka, hecto, and kilo, meaning, respectively, 10, 100, 1,000, and deci, centi, and milli, meaning, respectively, one-tenth, one-hundredth, and one-thousandth. Common metric prefixes can be found in Table A2.

The conversion factors presented in Table A3 can be used to calculate equivalents in various physical units commonly used in energy analyses. For example, 10 barrels are the equivalent of 420 U.S. gallons (10 barrels x 42 gallons/barrel = 420 gallons).

Table A1. Metric Conversion Factors

U.S. Unit	multiplied by	Conversion Factor	equals	Metric Unit	U.S. Unit	multiplied by	Conversion Factor	equals	Metric Unit
Mass					Volume				
short tons (2,000 lb)	x	0.907 184 7	=	metric tons (t)	barrels of oil (bbl)	x	0.158 987 3	=	cubic meters (cm ³)
long tons	x	1.016 047	=	metric tons (t)	cubic yards (yd ³)	x	0.764 555	=	cubic meters (cm ³)
pounds (lb)	x	0.453 592 37 ^a	=	kilograms (kg)	cubic feet (ft ³)	x	0.028 316 85	=	cubic meters (cm ³)
pounds uranium oxide (lb U ₃ O ₈)	x	0.384 647 ^b	=	kilograms uranium (kgU)	U.S. gallons (gal)	x	3.785 412	=	liters (L)
ounces, avoirdupois (avdp oz)	x	28.349 52	=	grams (g)	ounces, fluid (fl oz)	x	29.573 53	=	milliliters (mL)
					cubic inches (in ³)	x	16.387 06	=	milliliters (mL)
Length					Area				
miles (mi)	x	1.609 344 ^a	=	kilometers (km)	acres	x	0.404 69	=	hectares (ha)
yard (yd)	x	0.914 4 ^a	=	meters (m)	square miles (mi ²)	x	2.589 988	=	square kilometers (km ²)
feet (ft)	x	0.304 8 ^a	=	meters (m)	square yards (yd ²)	x	0.836 127 4	=	square meters (m ²)
inches (in)	x	2.54 ^a	=	centimeters (cm)	square feet (ft ²)	x	0.092 903 04 ^a	=	square meters (m ²)
					square inches (in ²)	x	6.451 6 ^a	=	square centimeters (cm ²)
Energy					Temperature				
British Thermal Units (Btu)	x	1,055.055 852 62 ^{a,c}	=	joules (J)	degrees Fahrenheit (°F)	x	5/9 (after subtracting 32) ^{a,d}	=	degrees Celsius (°C)
calories (cal)	x	4.186 8 ^a	=	joules (J)					
kilowatthours (kWh)	x	3.6 ^a	=	megajoules (MJ)					

^aExact conversion.

^bCalculated by the Energy Information Administration.

^cThe Btu used in this table is the International Table Btu adopted by the Fifth International Conference on Properties of Steam, London, 1956.

^dTo convert degrees Celsius (°C) to degrees Fahrenheit (°F) exactly, multiply by 9/5, then add 32.

Notes: • Spaces have been inserted after every third digit to the right of the decimal for ease of reading. • Most metric units shown belong to the International System of Units (SI),

and the liter, hectare, and metric ton are accepted for use with the SI units. For more information about the SI units, contact Dr. Barry Taylor at Building 221, Room B160, National Institute of Standards and Technology, Gaithersburg, MD 20899, or on telephone number 301-975-4220.

Sources: General Services Administration, Federal Standard 376B, *Preferred Metric Units for General Use by the Federal Government* (Washington, DC, January 27, 1993), pp. 9-11, 13, and 16. National Institute of Standards and Technology, Special Publications 330, 811, and 814. American National Standards Institute/Institute of Electrical and Electronic Engineers, ANSI/IEEE Std 268-1992, pp. 28 and 29.

Table A2. Metric Prefixes

Unit Multiple	Prefix	Symbol	Unit Subdivision	Prefix	Symbol
10 ¹	deka	da	10 ⁻¹	deci	d
10 ²	hecto	h	10 ⁻²	centi	c
10 ³	kilo	k	10 ⁻³	milli	m
10 ⁶	mega	M	10 ⁻⁶	micro	
10 ⁹	giga	G	10 ⁻⁹	nano	n
10 ¹²	tera	T	10 ⁻¹²	pico	p
10 ¹⁵	peta	P	10 ⁻¹⁵	femto	f
10 ¹⁸	exa	E	10 ⁻¹⁸	atto	a
10 ²¹	zetta	Z	10 ⁻²¹	zepto	z
10 ²⁴	yotta	Y	10 ⁻²⁴	yocto	Y

Source: U.S. Department of Commerce, National Institute of Standards and Technology, *The International System of Units (SI)*, NIST Special Publication 330, 1991 Edition

Table A3. Other Physical Conversion Factors

Energy Source	Original Unit		Conversion Factor		Final Unit
Petroleum	barrels (bbl)	x	42 ^a	=	U.S. gallons (gal)
Coal	short tons	x	2,000 ^a	=	pounds (lb)
	long tons	x	2,240 ^a	=	pounds (lb)
	metric tons (t)	x	1,000 ^a	=	kilograms (kg)
Wood	ords (cd)	x	1.25 ^b	=	short tons
	ords (cd)	x	128	=	cubic feet (ft ³)

^aExact conversion.

^bCalculated by the Energy Information Administration.

Source: U.S. Department of Commerce, National Institute of Standards and Technology, *Specifications, Tolerances and Other Technical Requirements for Weighing and Measuring Devices*, NIST Handbook 44, 1994 Edition (Washington, DC, October 1993), pp. B-10, C-17, and C-21.

