

## Glossary

**Acid stabilization:** A circumstance where the pH of the waste mixture in an animal manure management system is maintained near 7.0, optimal conditions for methane production.

**Aerobic bacteria:** Microorganisms living, active, or occurring only in the presence of oxygen.

**Aerobic decomposition:** The breakdown of a molecule into simpler molecules or atoms by microorganisms under favorable conditions of oxygenation.

**Aerosols:** Airborne particles.

**Afforestation:** Planting of new forests on lands that have not been recently forested.

**Agglomeration:** The clustering of disparate elements.

**Airshed:** An area or region defined by settlement patterns or geology that results in discrete atmospheric conditions.

**Albedo:** The fraction of incident light or electromagnetic radiation that is reflected by a surface or body. See *Planetary albedo*.

**Anaerobes:** Organisms that live and are active only in the absence of oxygen.

**Anaerobic bacteria:** Microorganisms living, active, or occurring only in the absence of oxygen.

**Anaerobic decomposition:** The breakdown of molecules into simpler molecules or atoms by microorganisms that can survive in the partial or complete absence of oxygen.

**Anaerobic lagoon:** A liquid-based manure management system, characterized by waste residing in water to a depth of at least six feet for a period ranging between 30 and 200 days.

**Anode:** A positive electrode, as in a battery, radio tube, etc.

**Anthracite:** The highest rank of coal; used primarily for residential and commercial space heating. It is a hard, brittle, and black lustrous coal, often referred to as hard coal, containing a high percentage of fixed carbon and a low percentage of volatile matter. The moisture content of fresh-mined anthracite generally is less than 15

percent. The heat content of anthracite ranges from 22 to 28 million Btu per ton on a moist, mineral-matter-free basis. The heat content of anthracite coal consumed in the United States averages 25 million Btu per ton, on the as-received basis (i.e., containing both inherent moisture and mineral matter). Note: Since the 1980's, anthracite refuse or mine waste has been used for steam electric power generation. This fuel typically has a heat content of 15 million Btu per ton or less.

**Anthropogenic:** Made or generated by a human or caused by human activity. The term is used in the context of global climate change to refer to gaseous emissions that are the result of human activities, as well as other potentially climate-altering activities, such as deforestation.

**API Gravity:** American Petroleum Institute measure of specific gravity of crude oil or condensate in degrees. An arbitrary scale expressing the gravity or density of liquid petroleum products. The measuring scale is calibrated in terms of degrees API; it is calculated as follows: Degrees API =  $(141.5/\text{sp.gr.}60 \text{ deg.F}/60 \text{ deg.F}) - 131.5$ .

**Asphalt:** A dark brown-to-black cement-like material obtained by petroleum processing and containing bitumens as the predominant component; used primarily for road construction. It includes crude asphalt as well as the following finished products: cements, fluxes, the asphalt content of emulsions (exclusive of water), and petroleum distillates blended with asphalt to make cut-back asphalts. Note: The conversion factor for asphalt is 5.5 barrels per short ton.

**Associated natural gas:** See *Associated-dissolved natural gas* and *Natural gas*.

**Associated-dissolved natural gas:** Natural gas that occurs in crude oil reservoirs either as free gas (associated) or as gas in solution with crude oil (dissolved gas). See *Natural gas*.

**Aviation gasoline (finished):** A complex mixture of relatively volatile hydrocarbons with or without small quantities of additives, blended to form a fuel suitable for use in aviation reciprocating engines. Fuel specifications are provided in ASTM Specification D 910 and Military Specification MIL-G-5572. Note: Data on blending components are not counted in data on finished aviation gasoline.

**Balancing item:** Represents differences between the sum of the components of natural gas supply and the sum of the components of natural gas disposition. These differences may be due to quantities lost or to the effects of data reporting problems. Reporting problems include differences due to the net result of conversions of flow data metered at varying temperature and pressure bases and converted to a standard temperature and pressure base; the effect of variations in company accounting and billing practices; differences between billing cycle and calendar period time frames; and imbalances resulting from the merger of data reporting systems that vary in scope, format, definitions, and type of respondents.

**Biofuels:** Liquid fuels and blending components produced from biomass (plant) feedstocks, used primarily for transportation.

**Biogas:** The gas produced from the anaerobic decomposition of organic material in a landfill.

**Biogenic:** Produced by the actions of living organisms.

**Biomass:** Organic nonfossil material of biological origin constituting a renewable energy source.

**Biosphere:** The portion of the Earth and its atmosphere that can support life. The part of the global carbon cycle that includes living organisms and biogenic organic matter.

**Bituminous coal:** A dense coal, usually black, sometimes dark brown, often with well-defined bands of bright and dull material, used primarily as fuel in steam-electric power generation, with substantial quantities also used for heat and power applications in manufacturing and to make coke. Bituminous coal is the most abundant coal in active U.S. mining regions. Its moisture content usually is less than 20 percent. The heat content of bituminous coal ranges from 21 to 30 million Btu per ton on a moist, mineral-matter-free basis. The heat content of bituminous coal consumed in the United States averages 24 million Btu per ton, on the as-received basis (i.e., containing both inherent moisture and mineral matter).

**BOD<sub>5</sub>:** The biochemical oxygen demand of wastewater during decomposition occurring over a 5-day period. A measure of the organic content of wastewater.

**Bromofluorocarbons (halons):** Inert, nontoxic chemicals that have at least one bromine atom in their chemical makeup. They evaporate without leaving a residue and are used in fire extinguishing systems, especially for large computer installations.

**Bunker fuel:** Fuel supplied to ships and aircraft, both domestic and foreign, consisting primarily of residual and distillate fuel oil for ships and kerosene-based jet

fuel for aircraft. The term “international bunker fuels” is used to denote the consumption of fuel for international transport activities. *Note:* For the purposes of greenhouse gas emissions inventories, data on emissions from combustion of international bunker fuels are subtracted from national emissions totals. Historically, bunker fuels have meant only ship fuel. See *Vessel bunkering*.

**Calcination:** A process in which a material is heated to a high temperature without fusing, so that hydrates, carbonates, or other compounds are decomposed and the volatile material is expelled.

**Calcium sulfate:** A white crystalline salt, insoluble in water. Used in Keene’s cement, in pigments, as a paper filler, and as a drying agent.

**Calcium sulfite:** A white powder, soluble in dilute sulfuric acid. Used in the sulfite process for the manufacture of wood pulp.

**Capital stock:** Property, plant and equipment used in the production, processing and distribution of energy resources.

**Carbon black:** An amorphous form of carbon, produced commercially by thermal or oxidative decomposition of hydrocarbons and used principally in rubber goods, pigments, and printer’s ink.

**Carbon budget:** Carbon budget: The balance of the exchanges (incomes and losses) of carbon between carbon sinks (e.g., atmosphere and biosphere) in the carbon cycle. See *Carbon cycle* and *Carbon sink*.

**Carbon cycle:** All carbon sinks and exchanges of carbon from one sink to another by various chemical, physical, geological, and biological processes. See *Carbon sink* and *Carbon budget*.

**Carbon dioxide (CO<sub>2</sub>):** A colorless, odorless, nonpoisonous gas that is a normal part of Earth’s atmosphere. Carbon dioxide is a product of fossil-fuel combustion as well as other processes. It is considered a greenhouse gas as it traps heat (infrared energy) radiated by the Earth into the atmosphere and thereby contributes to the potential for global warming. The global warming potential (GWP) of other greenhouse gases is measured in relation to that of carbon dioxide, which by international scientific convention is assigned a value of one (1). See *Global warming potential (GWP)* and *Greenhouse gases*.

**Carbon dioxide equivalent:** The amount of carbon dioxide by weight emitted into the atmosphere that would produce the same estimated radiative forcing as a given weight of another radiatively active gas. Carbon dioxide equivalents are computed by multiplying the weight of the gas being measured (for example, methane) by its

estimated global warming potential (which is 21 for methane). “Carbon equivalent units” are defined as carbon dioxide equivalents multiplied by the carbon content of carbon dioxide (i.e., 12/44).

**Carbon flux:** See *Carbon budget*.

**Carbon intensity:** The amount of carbon by weight emitted per unit of energy consumed. A common measure of carbon intensity is weight of carbon per British thermal unit (Btu) of energy. When there is only one fossil fuel under consideration, the carbon intensity and the emissions coefficient are identical. When there are several fuels, carbon intensity is based on their combined emissions coefficients weighted by their energy consumption levels. See *Emissions coefficient* and *Carbon output rate*.

**Carbon output rate:** The amount of carbon by weight per kilowatthour of electricity produced.

**Carbon sequestration:** The fixation of atmospheric carbon dioxide in a carbon sink through biological or physical processes.

**Carbon sink:** A reservoir that absorbs or takes up released carbon from another part of the carbon cycle. The four sinks, which are regions of the Earth within which carbon behaves in a systematic manner, are the atmosphere, terrestrial biosphere (usually including freshwater systems), oceans, and sediments (including fossil fuels).

**Catalytic converter:** A device containing a catalyst for converting automobile exhaust into mostly harmless products.

**Catalytic hydrocracking:** A refining process that uses hydrogen and catalysts with relatively low temperatures and high pressures for converting middle boiling or residual material to high octane gasoline, reformer charge stock, jet fuel, and/or high grade fuel oil. The process uses one or more catalysts, depending on product output, and can handle high sulfur feedstocks without prior desulfurization.

**Cesspool:** An underground reservoir for liquid waste, typically household sewage.

**Chlorofluorocarbon (CFC):** Any of various compounds consisting of carbon, hydrogen, chlorine, and fluorine used as refrigerants. CFCs are now thought to be harmful to the earth’s atmosphere.

**Clean Development Mechanism (CDM):** A Kyoto Protocol program that enables industrialized countries to finance emissions-avoiding projects in developing countries and receive credit for reductions achieved against

their own emissions limitation targets. See *Kyoto Protocol*.

**Climate:** The average course or condition of the weather over a period of years as exhibited by temperature, humidity, wind velocity, and precipitation.

**Climate change:** A term used to refer to all forms of climatic inconsistency, but especially to significant change from one prevailing climatic condition to another. In some cases, “climate change” has been used synonymously with the term “global warming”; scientists, however, tend to use the term in a wider sense inclusive of natural changes in climate, including climatic cooling.

**Clinker:** Powdered cement, produced by heating a properly proportioned mixture of finely ground raw materials (calcium carbonate, silica, alumina, and iron oxide) in a kiln to a temperature of about 2,700°F.

**Cloud condensation nuclei:** Aerosol particles that provide a platform for the condensation of water vapor, resulting in clouds with higher droplet concentrations and increased albedo.

**Coal coke:** See *Coke (coal)*.

**Coalbed methane:** Methane is generated during coal formation and is contained in the coal microstructure. Typical recovery entails pumping water out of the coal to allow the gas to escape. Methane is the principal component of natural gas. Coalbed methane can be added to natural gas pipelines without any special treatment.

**Coke (coal):** A solid carbonaceous residue derived from low-ash, low-sulfur bituminous coal from which the volatile constituents are driven off by baking in an oven at temperatures as high as 2,000 degrees Fahrenheit so that the fixed carbon and residual ash are fused together. Coke is used as a fuel and as a reducing agent in smelting iron ore in a blast furnace. Coke from coal is grey, hard, and porous and has a heating value of 24.8 million Btu per ton.

**Coke (petroleum):** A residue high in carbon content and low in hydrogen that is the final product of thermal decomposition in the condensation process in cracking. This product is reported as marketable coke or catalyst coke. The conversion is 5 barrels (of 42 U.S. gallons each) per short ton. Coke from petroleum has a heating value of 6.024 million Btu per barrel.

**Combustion:** Chemical oxidation accompanied by the generation of light and heat.

**Combustion chamber:** An enclosed vessel in which chemical oxidation of fuel occurs.

**Conference of the Parties (COP):** The collection of nations that have ratified the Framework Convention on Climate Change (FCCC). The primary role of the COP is to keep implementation of the FCCC under review and make the decisions necessary for its effective implementation. See *Framework Convention on Climate Change (FCCC)*.

**Cracking:** The refining process of breaking down the larger, heavier, and more complex hydrocarbon molecules into simpler and lighter molecules.

**Criteria pollutant:** A pollutant determined to be hazardous to human health and regulated under EPA's National Ambient Air Quality Standards. The 1970 amendments to the Clean Air Act require EPA to describe the health and welfare impacts of a pollutant as the "criteria" for inclusion in the regulatory regime.

**Crop residue:** Organic residue remaining after the harvesting and processing of a crop.

**Cultivar:** A horticulturally or agriculturally derived variety of a plant.

**Deforestation:** The net removal of trees from forested land.

**Degasification system:** The methods employed for removing methane from a coal seam that could not otherwise be removed by standard ventilation fans and thus would pose a substantial hazard to coal miners. These systems may be used prior to mining or during mining activities.

**Degradable organic carbon:** The portion of organic carbon present in such solid waste as paper, food waste, and yard waste that is susceptible to biochemical decomposition.

**Desulfurization:** The removal of sulfur, as from molten metals, petroleum oil, or flue gases.

**Diffusive transport:** The process by which particles of liquids or gases move from an area of higher concentration to an area of lower concentration.

**Distillate fuel:** A general classification for one of the petroleum fractions produced in conventional distillation operations. It includes diesel fuels and fuel oils. Products known as No. 1, No. 2, and No. 4 diesel fuel are used in on-highway diesel engines, such as those in trucks and automobiles, as well as off-highway engines, such as those in railroad locomotives and agricultural machinery. Products known as No. 1, No. 2, and No. 4 fuel oils are used primarily for space heating and electric power generation.

**Efflux:** An outward flow.

**Electrical generating capacity:** The full-load continuous power rating of electrical generating facilities, generators, prime movers, or other electric equipment (individually or collectively).

**EMCON Methane Generation Model:** A model for estimating the production of methane from municipal solid waste landfills.

**Emissions:** Anthropogenic releases of gases to the atmosphere. In the context of global climate change, they consist of radiatively important greenhouse gases (e.g., the release of carbon dioxide during fuel combustion).

**Emissions coefficient:** A unique value for scaling emissions to activity data in terms of a standard rate of emissions per unit of activity (e.g., pounds of carbon dioxide emitted per Btu of fossil fuel consumed).

**Enteric fermentation:** A digestive process by which carbohydrates are broken down by microorganisms into simple molecules for absorption into the bloodstream of an animal.

**Eructation:** An act or instance of belching.

**ETBE (ethyl tertiary butyl ether):**  $(\text{CH}_3)_3\text{COC}_2\text{H}$ : An oxygenate blend stock formed by the catalytic etherification of isobutylene with ethanol.

**Ethylene:** An olefinic hydrocarbon recovered from refinery processes or petrochemical processes. Ethylene is used as a petrochemical feedstock for numerous chemical applications and the production of consumer goods.

**Ethylene dichloride:** A colorless, oily liquid used as a solvent and fumigant for organic synthesis, and for ore flotation.

**Facultative bacteria:** Bacteria that grow equally well under aerobic and anaerobic conditions.

**Flange:** A rib or a rim for strength, for guiding, or for attachment to another object (e.g., on a pipe).

**Flared:** Gas disposed of by burning in flares usually at the production sites or at gas processing plants.

**Flatus:** Gas generated in the intestines or the stomach of an animal.

**Flue gas desulfurization:** Equipment used to remove sulfur oxides from the combustion gases of a boiler plant before discharge to the atmosphere. Also referred to as scrubbers. Chemicals such as lime are used as scrubbing media.

**Fluidized-bed combustion:** A method of burning particulate fuel, such as coal, in which the amount of air



required for combustion far exceeds that found in conventional burners. The fuel particles are continually fed into a bed of mineral ash in the proportions of 1 part fuel to 200 parts ash, while a flow of air passes up through the bed, causing it to act like a turbulent fluid.

**Flux material:** A substance used to promote fusion, e.g., of metals or minerals.

**Fodder:** Coarse food for domestic livestock.

**Forestomach:** See *Rumen*.

**Fossil fuel:** An energy source formed in the earth's crust from decayed organic material. The common fossil fuels are petroleum, coal, and natural gas.

**Framework Convention on Climate Change (FCCC):** An agreement opened for signature at the "Earth Summit" in Rio de Janeiro, Brazil, on June 4, 1992, which has the goal of stabilizing greenhouse gas concentrations in the atmosphere at a level that would prevent significant anthropogenically forced climate change. See *Climate change*.

**Fuel cycle:** The entire set of sequential processes or stages involved in the utilization of fuel, including extraction, transformation, transportation, and combustion. Emissions generally occur at each stage of the fuel cycle.

**Fugitive emissions:** Unintended leaks of gas from the processing, transmission, and/or transportation of fossil fuels.

**Gasification:** A method for converting coal, petroleum, biomass, wastes, or other carbon-containing materials into a gas that can be burned to generate power or processed into chemicals and fuels.

**Gate station:** Location where the pressure of natural gas being transferred from the transmission system to the distribution system is lowered for transport through small diameter, low pressure pipelines.

**Geothermal:** Pertaining to heat within the Earth.

**Global climate change:** See *Climate change*.

**Global warming:** An increase in the near surface temperature of the Earth. Global warming has occurred in the distant past as the result of natural influences, but the term is today most often used to refer to the warming that some scientists predict will occur as a result of increased anthropogenic emissions of greenhouse gases. See *Climate change*.

**Global warming potential (GWP):** An index used to compare the relative radiative forcing of different gases without directly calculating the changes in atmospheric

concentrations. GWPs are calculated as the ratio of the radiative forcing that would result from the emission of one kilogram of a greenhouse gas to that from the emission of one kilogram of carbon dioxide over a fixed period of time, such as 100 years.

**Greenhouse effect:** The result of water vapor, carbon dioxide, and other atmospheric gases trapping radiant (infrared) energy, thereby keeping the earth's surface warmer than it would otherwise be. Greenhouse gases within the lower levels of the atmosphere trap this radiation, which would otherwise escape into space, and subsequent re-radiation of some of this energy back to the Earth maintains higher surface temperatures than would occur if the gases were absent. See *Greenhouse gases*.

**Greenhouse gases:** Those gases, such as water vapor, carbon dioxide, nitrous oxide, methane, hydrofluorocarbons (HFCs), perfluorocarbons (PFCs) and sulfur hexafluoride, that are transparent to solar (short-wave) radiation but opaque to long-wave (infrared) radiation, thus preventing long-wave radiant energy from leaving the Earth's atmosphere. The net effect is a trapping of absorbed radiation and a tendency to warm the planet's surface.

**Gross gas withdrawal:** The full-volume of compounds extracted at the wellhead, including nonhydrocarbon gases and natural gas plant liquids.

**Gypsum:** Calcium sulfate dihydrate ( $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ ), a sludge constituent from the conventional lime scrubber process, obtained as a byproduct of the dewatering operation and sold for commercial use.

**Halogenated substances:** A volatile compound containing halogens, such as chlorine, fluorine or bromine.

**Halons:** See *Bromofluorocarbons*.

**Heating degree-days (HDD):** A measure of how cold a location is over a period of time relative to a base temperature, most commonly specified as 65 degrees Fahrenheit. The measure is computed for each day by subtracting the average of the day's high and low temperatures from the base temperature (65 degrees), with negative values set equal to zero. Each day's heating degree-days are summed to create a heating degree-day measure for a specified reference period. Heating degree-days are used in energy analysis as an indicator of space heating energy requirements or use.

**Herbivore:** A plant-eating animal.

**Hydrocarbon:** An organic chemical compound of hydrogen and carbon in either gaseous, liquid, or solid phase. The molecular structure of hydrocarbon compounds varies from the simple (e.g., methane, a

constituent of natural gas) to the very heavy and very complex.

**Hydrochlorofluorocarbons (HCFCs):** Chemicals composed of one or more carbon atoms and varying numbers of hydrogen, chlorine, and fluorine atoms.

**Hydrofluorocarbons (HFCs):** A group of man-made chemicals composed of one or two carbon atoms and varying numbers of hydrogen and fluorine atoms. Most HFCs have 100-year Global Warming Potentials in the thousands.

**Hydroxyl radical (OH):** An important chemical scavenger of many trace gases in the atmosphere that are greenhouse gases. Atmospheric concentrations of OH affect the atmospheric lifetimes of greenhouse gases, their abundance, and, ultimately, the effect they have on climate.

**Intergovernmental Panel on Climate Change (IPCC):** A panel established jointly in 1988 by the World Meteorological Organization and the United Nations Environment Program to assess the scientific information relating to climate change and to formulate realistic response strategies.

**International bunker fuels:** See *Bunker fuels*.

**Jet fuel:** A refined petroleum product used in jet aircraft engines. It includes kerosene-type jet fuel and naphtha-type jet fuel.

**Joint Implementation (JI):** Agreements made between two or more nations under the auspices of the Framework Convention on Climate Change (FCCC) whereby a developed country can receive "emissions reduction units" when it helps to finance projects that reduce net emissions in another developed country (including countries with economies in transition).

**Kerosene:** A light petroleum distillate that is used in space heaters, cook stoves, and water heaters and is suitable for use as a light source when burned in wick-fed lamps. Kerosene has a maximum distillation temperature of 400 degrees Fahrenheit at the 10-percent recovery point, a final boiling point of 572 degrees Fahrenheit, and a minimum flash point of 100 degrees Fahrenheit. Included are No. 1-K and No. 2-K, the two grades recognized by ASTM Specification D 3699 as well as all other grades of kerosene called range or stove oil, which have properties similar to those of No. 1 fuel oil. See *Kerosene-type jet fuel*.

**Kerosene-type jet fuel:** A kerosene-based product having a maximum distillation temperature of 400 degrees Fahrenheit at the 10-percent recovery point and a final maximum boiling point of 572 degrees Fahrenheit and meeting ASTM Specification D 1655 and Military

Specifications MIL-T-5624P and MIL-T-83133D (Grades JP-5 and JP-8). It is used for commercial and military turbojet and turboprop aircraft engines.

**Kyoto Protocol:** The result of negotiations at the third Conference of the Parties (COP-3) in Kyoto, Japan, in December of 1997. The Kyoto Protocol sets binding greenhouse gas emissions targets for countries that sign and ratify the agreement. The gases covered under the Protocol include carbon dioxide, methane, nitrous oxide, hydrofluorocarbons (HFCs), perfluorocarbons (PFCs) and sulfur hexafluoride.

**Ketone-alcohol (cyclohexanol):** An oily, colorless, hygroscopic liquid with a camphor-like odor. Used in soapmaking, dry cleaning, plasticizers, insecticides, and germicides.

**Leachate:** The liquid that has percolated through the soil or other medium.

**Lignite:** The lowest rank of coal, often referred to as brown coal, used almost exclusively as fuel for steam-electric power generation. It is brownish-black and has a high inherent moisture content, sometimes as high as 45 percent. The heat content of lignite ranges from 9 to 17 million Btu per ton on a moist, mineral-matter-free basis. The heat content of lignite consumed in the United States averages 13 million Btu per ton, on the as-received basis (i.e., containing both inherent moisture and mineral matter).

**Liquefied petroleum gases:** A group of hydrocarbon-based gases derived from crude oil refining or natural gas fractionation. They include ethane, ethylene, propane, propylene, normal butane, butylene, isobutane, and isobutylene. For convenience of transportation, these gases are liquefied through pressurization.

**Lubricants:** Substances used to reduce friction between bearing surfaces, or incorporated into other materials used as processing aids in the manufacture of other products, or used as carriers of other materials. Petroleum lubricants may be produced either from distillates or residues. Lubricants include all grades of lubricating oils, from spindle oil to cylinder oil to those used in greases.

**Methane:** A colorless, flammable, odorless hydrocarbon gas (CH<sub>4</sub>) which is the major component of natural gas. It is also an important source of hydrogen in various industrial processes. Methane is a greenhouse gas. See also *Greenhouse gases*.

**Methanogens:** Bacteria that synthesize methane, requiring completely anaerobic conditions for growth.

**Methanol:** A light alcohol that can be used for gasoline blending. See oxygenate.

**Methanotrophs:** Bacteria that use methane as food and oxidize it into carbon dioxide.

**Methyl chloroform (trichloroethane):** An industrial chemical ( $\text{CH}_3\text{CCl}_3$ ) used as a solvent, aerosol propellant, and pesticide and for metal degreasing.

**Methyl tertiary butyl ether (MTBE):** A colorless, flammable, liquid oxygenated hydrocarbon containing 18.15 percent oxygen.

**Methylene chloride:** A colorless liquid, nonexplosive and practically nonflammable. Used as a refrigerant in centrifugal compressors, a solvent for organic materials, and a component in nonflammable paint removers.

**Mole:** The quantity of a compound or element that has a weight in grams numerically equal to its molecular weight. Also referred to as gram molecule or gram molecular weight.

**Montreal Protocol:** The Montreal Protocol on Substances that Deplete the Ozone Layer (1987). An international agreement, signed by most of the industrialized nations, to substantially reduce the use of chlorofluorocarbons (CFCs). Signed in January 1989, the original document called for a 50-percent reduction in CFC use by 1992 relative to 1986 levels. The subsequent London Agreement called for a complete elimination of CFC use by 2000. The Copenhagen Agreement, which called for a complete phaseout by January 1, 1996, was implemented by the U.S. Environmental Protection Agency.

**Motor gasoline (finished):** A complex mixture of relatively volatile hydrocarbons with or without small quantities of additives, blended to form a fuel suitable for use in spark-ignition engines. Motor gasoline, as defined in ASTM Specification D 4814 or Federal Specification VV-G-1690C, is characterized as having a boiling range of 122 to 158 degrees Fahrenheit at the 10 percent recovery point to 365 to 374 degrees Fahrenheit at the 90 percent recovery point. "Motor Gasoline" includes conventional gasoline; all types of oxygenated gasoline, including gasohol; and reformulated gasoline, but excludes aviation gasoline. Note: Volumetric data on blending components, such as oxygenates, are not counted in data on finished motor gasoline until the blending components are blended into the gasoline.

**Multiple cropping:** A system of growing several crops on the same field in one year.

**Municipal solid waste:** Residential solid waste and some nonhazardous commercial, institutional, and industrial wastes.

**Naphtha less than 401 degrees Fahrenheit:** A naphtha with a boiling range of less than 401 degrees Fahrenheit that is intended for use as a petrochemical feedstock. Also see *Petrochemical feedstocks*.

**Naphtha-type jet fuel:** A fuel in the heavy naphtha boiling range having an average gravity of 52.8 degrees API, 20 to 90 percent distillation temperatures of 290 degrees to 470 degrees Fahrenheit, and meeting Military Specification MIL-T-5624L (Grade JP-4). It is used primarily for military turbojet and turboprop aircraft engines because it has a lower freeze point than other aviation fuels and meets engine requirements at high altitudes and speeds.

**Natural gas:** A mixture of hydrocarbons and small quantities of various nonhydrocarbons in the gaseous phase or in solution with crude oil in natural underground reservoirs.

**Natural gas liquids (NGLs):** Those hydrocarbons in natural gas that are separated as liquids from the gas. Includes natural gas plant liquids and lease condensate.

**Natural gas, pipeline quality:** A mixture of hydrocarbon compounds existing in the gaseous phase with sufficient energy content, generally above 900 Btu, and a small enough share of impurities for transport through commercial gas pipelines and sale to end-users.

**Nitrogen oxides ( $\text{NO}_x$ ):** Compounds of nitrogen and oxygen produced by the burning of fossil fuels.

**Nitrous oxide ( $\text{N}_2\text{O}$ ):** A colorless gas, naturally occurring in the atmosphere. Nitrous oxide has a 100-year Global Warming Potential of 310.

**Nonmethane volatile organic compounds (NMVOCs):** Organic compounds, other than methane, that participate in atmospheric photochemical reactions.

**Octane:** A flammable liquid hydrocarbon found in petroleum. Used as a standard to measure the anti-knock properties of motor fuel.

**Oil reservoir:** An underground pool of liquid consisting of hydrocarbons, sulfur, oxygen, and nitrogen trapped within a geological formation and protected from evaporation by the overlying mineral strata.

**Organic content:** The share of a substance that is of animal or plant origin.

**Organic waste:** Waste material of animal or plant origin.

**Oxidize:** To chemically transform a substance by combining it with oxygen.

**Oxygenates:** Substances which, when added to gasoline, increase the amount of oxygen in that gasoline blend. Ethanol, Methyl Tertiary Butyl Ether (MTBE), Ethyl Tertiary Butyl Ether (ETBE), and methanol are common oxygenates.

**Ozone:** A molecule made up of three atoms of oxygen. Occurs naturally in the stratosphere and provides a



protective layer shielding the Earth from harmful ultraviolet radiation. In the troposphere, it is a chemical oxidant, a greenhouse gas, and a major component of photochemical smog.

**Ozone precursors:** Chemical compounds, such as carbon monoxide, methane, nonmethane hydrocarbons, and nitrogen oxides, which in the presence of solar radiation react with other chemical compounds to form ozone.

**Paraffinic hydrocarbons:** Straight-chain hydrocarbon compounds with the general formula  $C_nH_{2n+2}$ .

**Perfluorocarbons (PFCs):** A group of man-made chemicals composed of one or two carbon atoms and four to six fluorine atoms, containing no chlorine. PFCs have no commercial uses and are emitted as a byproduct of aluminum smelting and semiconductor manufacturing. PFCs have very high 100-year Global Warming Potentials and are very long-lived in the atmosphere.

**Perfluoromethane:** A compound ( $CF_4$ ) emitted as a byproduct of aluminum smelting.

**Petrochemical feedstocks:** Chemical feedstocks derived from petroleum principally for the manufacture of chemicals, synthetic rubber, and a variety of plastics.

**Petroleum:** A broadly defined class of liquid hydrocarbon mixtures. Included are crude oil, lease condensate, unfinished oils, refined products obtained from the processing of crude oil, and natural gas plant liquids. Note: Volumes of finished petroleum products include nonhydrocarbon compounds, such as additives and detergents, after they have been blended into the products.

**Petroleum coke:** See *Coke (petroleum)*.

**Photosynthesis:** The manufacture by plants of carbohydrates and oxygen from carbon dioxide and water in the presence of chlorophyll, with sunlight as the energy source. Carbon is sequestered and oxygen and water vapor are released in the process.

**Pig iron:** Crude, high-carbon iron produced by reduction of iron ore in a blast furnace.

**Pipeline, distribution:** A pipeline that conveys gas from a transmission pipeline to its ultimate consumer.

**Pipeline, gathering:** A pipeline that conveys gas from a production well/field to a gas processing plant or transmission pipeline for eventual delivery to end-use consumers.

**Pipeline, transmission:** A pipeline that conveys gas from a region where it is produced to a region where it is to be distributed.

**Planetary albedo:** The fraction of incident solar radiation that is reflected by the Earth-atmosphere system and returned to space, mostly by backscatter from clouds in the atmosphere.

**Pneumatic device:** A device moved or worked by air pressure.

**Polystyrene:** A polymer of styrene that is a rigid, transparent thermoplastic with good physical and electrical insulating properties, used in molded products, foams, and sheet materials.

**Polyvinyl chloride (PVC):** A polymer of vinyl chloride. Tasteless, odorless, insoluble in most organic solvents. A member of the family vinyl resin, used in soft flexible films for food packaging and in molded rigid products, such as pipes, fibers, upholstery, and bristles.

**Post-mining emissions:** Emissions of methane from coal occurring after the coal has been mined, during transport or pulverization.

**Radiative forcing:** A change in average net radiation at the top of the troposphere (known as the tropopause) because of a change in either incoming solar or exiting infrared radiation. A positive radiative forcing tends on average to warm the earth's surface; a negative radiative forcing on average tends to cool the earth's surface. Greenhouse gases, when emitted into the atmosphere, trap infrared energy radiated from the earth's surface and therefore tend to produce positive radiative forcing. See *Greenhouse gases*.

**Radiatively active gases:** Gases that absorb incoming solar radiation or outgoing infrared radiation, affecting the vertical temperature profile of the atmosphere. See *Radiative forcing*.

**Ratoon crop:** A crop cultivated from the shoots of a perennial plant.

**Redox potential:** A measurement of the state of oxidation of a system.

**Reflectivity:** The ratio of the energy carried by a wave after reflection from a surface to its energy before reflection.

**Reforestation:** Replanting of forests on lands that have recently been harvested or otherwise cleared of trees.

**Reformulated gasoline:** Finished motor gasoline formulated for use in motor vehicles, the composition and properties of which meet the requirements of the reformulated gasoline regulations promulgated by the U.S. Environmental Protection Agency under Section 211(k) of the Clean Air Act. Note: This category includes oxygenated fuels program reformulated gasoline (OPRG)



but excludes reformulated gasoline blendstock for oxygenate blending (RBOB).

**Renewable energy resources:** Energy resources that are naturally replenishing but flow-limited. They are virtually inexhaustible in duration but limited in the amount of energy that is available per unit of time. Renewable energy resources include: biomass, hydro, geothermal, solar, wind, ocean thermal, wave action, and tidal action.

**Residual fuel oil:** A general classification for the heavier oils, known as No. 5 and No. 6 fuel oils, that remain after the distillate fuel oils and lighter hydrocarbons are distilled away in refinery operations. It conforms to ASTM Specifications D 396 and D 975 and Federal Specification VV-F-815C. No. 5, a residual fuel oil of medium viscosity, is also known as Navy Special and is defined in Military Specification MIL-F-859E, including Amendment 2 (NATO Symbol F-770). It is used in steam-powered vessels in government service and inshore powerplants. No. 6 fuel oil includes Bunker C fuel oil and is used for the production of electric power, space heating, vessel bunkering, and various industrial purposes.

**Rumen:** The large first compartment of the stomach of certain animals in which cellulose is broken down by the action of bacteria.

**Sample:** A set of measurements or outcomes selected from a given population.

**Sequestration:** See *Carbon sequestration*.

**Septic tank:** A tank in which the solid matter of continuously flowing sewage is disintegrated by bacteria.

**Sinter:** A chemical sedimentary rock deposited by precipitation from mineral waters, especially siliceous sinter and calcareous sinter.

**Sodium silicate:** A grey-white powder soluble in alkali and water, insoluble in alcohol and acid. Used to fireproof textiles, in petroleum refining and corrugated paperboard manufacture, and as an egg preservative. Also referred to as liquid glass, silicate of soda, sodium metasilicate, soluble glass, and water glass.

**Sodium tripolyphosphate:** A white powder used for water softening and as a food additive and texturizer.

**Stabilization lagoon:** A shallow artificial pond used for the treatment of wastewater. Treatment includes removal of solid material through sedimentation, the decomposition of organic material by bacteria, and the removal of nutrients by algae.

**Still gas (refinery gas):** Any form or mixture of gases produced in refineries by distillation, cracking,

reforming, and other processes. The principal constituents are methane, ethane, ethylene, normal butane, butylene, propane, propylene, etc. Still gas is used as a refinery fuel and a petrochemical feedstock. The conversion factor is 6 million Btu per fuel oil equivalent barrel.

**Stratosphere:** The region of the upper atmosphere extending from the tropopause (8 to 15 kilometers altitude) to about 50 kilometers. Its thermal structure, which is determined by its radiation balance, is generally very stable with low humidity.

**Stripper well:** An oil or gas well that produces at relatively low rates. For oil, stripper production is usually defined as production rates of between 5 and 15 barrels of oil per day. Stripper gas production would generally be anything less than 60 thousand cubic feet per day.

**Styrene:** A colorless, toxic liquid with a strong aromatic aroma. Insoluble in water, soluble in alcohol and ether; polymerizes rapidly; can become explosive. Used to make polymers and copolymers, polystyrene plastics, and rubber.

**Subbituminous coal:** A coal whose properties range from those of lignite to those of bituminous coal and used primarily as fuel for steam-electric power generation. It may be dull, dark brown to black, soft and crumbly, at the lower end of the range, to bright, jet black, hard, and relatively strong, at the upper end. Subbituminous coal contains 20 to 30 percent inherent moisture by weight. The heat content of subbituminous coal ranges from 17 to 24 million Btu per ton on a moist, mineral-matter-free basis. The heat content of subbituminous coal consumed in the United States averages 17 to 18 million Btu per ton, on the as-received basis (i.e., containing both inherent moisture and mineral matter).

**Sulfur dioxide (SO<sub>2</sub>):** A toxic, irritating, colorless gas soluble in water, alcohol, and ether. Used as a chemical intermediate, in paper pulping and ore refining, and as a solvent.

**Sulfur hexafluoride (SF<sub>6</sub>):** A colorless gas soluble in alcohol and ether, and slightly less soluble in water. It is used as a dielectric in electronics. It possesses the highest 100-year Global Warming Potential of any gas (23,900).

**Sulfur oxides (SO<sub>x</sub>):** Compounds containing sulfur and oxygen, such as sulfur dioxide (SO<sub>2</sub>) and sulfur trioxide (SO<sub>3</sub>).

**Tertiary amyl methyl ether ((CH<sub>3</sub>)<sub>2</sub>(C<sub>2</sub>H<sub>5</sub>)COCH<sub>3</sub>):** An oxygenate blend stock formed by the catalytic etherification of isoamylene with methanol.

**Troposphere:** The inner layer of the atmosphere below about 15 kilometers, within which there is normally a steady decrease of temperature with increasing altitude.

Nearly all clouds form and weather conditions manifest themselves within this region. Its thermal structure is caused primarily by the heating of the earth's surface by solar radiation, followed by heat transfer through turbulent mixing and convection.

**Uncertainty:** A measure used to quantify the plausible maximum and minimum values for emissions from any source, given the biases inherent in the methods used to calculate a point estimate and known sources of error.

**Vapor displacement:** The release of vapors that had previously occupied space above liquid fuels stored in tanks. These releases occur when tanks are emptied and filled.

**Ventilation system:** A method for reducing methane concentrations in coal mines to non-explosive levels by blowing air across the mine face and using large exhaust fans to remove methane while mining operations proceed.

**Vessel bunkering:** Includes sales for the fueling of commercial or private boats, such as pleasure craft, fishing boats, tugboats, and ocean-going vessels, including vessels operated by oil companies. Excluded are volumes sold to the U.S. Armed Forces.

**Volatile organic compounds (VOCs):** Organic compounds that participate in atmospheric photochemical reactions.

**Volatile solids:** A solid material that is readily decomposable at relatively low temperatures.

**Waste flow:** Quantity of a waste stream generated by an activity.

**Wastewater:** Water that has been used and contains dissolved or suspended waste materials.

**Wastewater, domestic and commercial:** Wastewater (sewage) produced by domestic and commercial establishments.

**Wastewater, industrial:** Wastewater produced by industrial processes.

**Water vapor:** Water in a vaporous form, especially when below boiling temperature and diffused (e.g., in the atmosphere).

**Wax:** A solid or semi-solid material derived from petroleum distillates or residues by such treatments as chilling, precipitating with a solvent, or de-oiling. It is a light-colored, more-or-less translucent crystalline mass, slightly greasy to the touch, consisting of a mixture of solid hydrocarbons in which the paraffin series predominates. Includes all marketable wax, whether crude scale or fully refined. The three grades included are microcrystalline, crystalline-fully refined, and crystalline-other. The conversion factor is 280 pounds per 42 U.S. gallons per barrel.

**Weanling system:** A cattle management system that places calves on feed starting at 165 days of age and continues until the animals have reached slaughter weight.

**Wellhead:** The point at which the crude (and/or natural gas) exits the ground. Following historical precedent, the volume and price for crude oil production are labeled as "wellhead," even though the cost and volume are now generally measured at the lease boundary. In the context of domestic crude price data, the term "wellhead" is the generic term used to reference the production site or lease property.

**Wetlands:** Areas regularly saturated by surface or groundwater and subsequently characterized by a prevalence of vegetation adapted for life in saturated-soil conditions.

**Wood energy:** Wood and wood products used as fuel, including roundwood (cordwood), limbwood, wood chips, bark, sawdust, forest residues, charcoal, pulp waste, and spent pulping liquor..

**Yearling system:** A cattle management system that includes a stocker period from 165 days of age to 425 days of age followed by a 140-day feedlot period.