

## **BID LIST NO. 0540**

### **SPECIFICATION**

#### **Property No. 25320-1**

##### Die Cut Labels, Pressure-Sensitive Adhesive

##### Label Paper (Ultra-smooth Uncoated Litho)

Stock: Reclaimed fiber, in any percentage is permitted, provided that the requirements of this standard are met.

Grammage: Grams per square meter (gsm)...67

Equivalent 25x38-500 (pounds)...45

A tolerance of +/-5% shall be allowed

Adhesive: Shall be a pressure-sensitive adhesive suitable for adhering tightly to paper, corrugated containers, and packaging films.

##### Construction

Labels shall be die cut 70 x 102 mm (2-3/4" x 4"). A tolerance of +/-3 mm (1/8") shall be allowed. The labels shall be spaced 3mm (1/8") apart on the backing sheet. There shall be no missing labels on the backing sheet. On the back of the backing sheet, there shall be a black "sensing" mark located at the space between the labels across the entire width of the backing sheet.

Roll size: Diameter shall be 185 mm (7-1/4") maximum. Width shall be 76mm (3"). The labels shall be tightly wound on an m (3") core at even tension with; the labels facing in. Each roll shall contain a minimum of 1,000 labels.

Use Information: This material shall be used on the Sato Model #4510 Thermal printer.

Sample Information: Each bidder shall submit a sample roll of label paper to show the quality of the material and construction of the product they propose to furnish.

Testing and Reference: paper testing shall be conducted in accordance with the applicable Technical Association of the Pulp and Paper Industry (TAPPI) testing standards, unless otherwise specified. These standards may be obtained from TAPPI, PO Box 105113, Atlanta, GA 30348. Note, all testing and measurements are made against the primary requirements, whether in gsm, mm, etc. The equivalent values are provided for informational purposes only.

##### Qualified Product

York Tape and Label Co.'s Product 015 is acceptable.