

Additional Requirements for Multistop Van Truck, 4x2

The body shall be constructed of sheet aluminum or magnesium alloys of equal strength (minimum 1 mm (0.040 in) roof, 2.5 mm (0.100 in) side panels and with an aluminum frame. The roof shall be supported by 4 integral longitudinal ribs and metal roof reinforcements which are bonded in place on 61 cm (24 in) spacing front to rear. Nose section of body may be molded fiberglass construction. Upholstered seat/backs driver, and assistant seats, set on posts shall be provided. Driver seat shall be adjustable fore and aft, and for height, with positive locking device to secure seat in place when in use. Both seats shall be provided with 3 point safety belts. The cab compartment shall be furnished with a minimum 32,000 BTU rated heater. Dome lights shall be provided: one in the driver's compartment/ one centered in the load space (Item 131)/ and two load space lights, equally spaced; for Items 134 and 134B. Dual adjustable combination (flat and convex) swing away mirrors shall be furnished. These multistop trucks shall be furnished with clearance lamps and side marker lamps conforming to FMVSS 108, regardless of width. Inset steps shall be provided at both front entrances, and shall have skid resistant (tread plate or non-skid material) surface. Body shall have sliding type front doors. The door operating handles shall be capable of serving as door opening/closing handles, or door grab handles shall be provided. All doors shall be furnished with cylinder type locks for the same key, with unlike keys on vehicles to the same destination. Sliding windows with not less than 2340 sq cm (360 sq in) of clear glass shall be provided in the front doors. All door windows shall be safety glass mounted in molded rubber in the upper section of the doors. Windows shall be watertight.

Rear door clear opening shall be a minimum of 89 cm (35 in) wide and 165 cm (65 in) high. Rear door(s) shall open 180° and have door check to hold door in full open position. Grab handle shall be provided on inside of rear door, in addition to door latch operating handle, to assist in closing door(s).

A safety-tread, steel plate step, integrated with the rear bumper and extending not less than 84 cm (33 in) in width, shall be furnished. Rear end splash shields shall be provided extending from ends of steps to outside edges of the body and shall be mounted independent of the body.

Means of access shall be provided in the engine compartment for complete engine service and maintenance; and for servicing at least the radiator, engine oil, transmission oil, washer fluid, power steering fluid, etc., from the exterior front of the vehicle.

Not less than five full width crossmembers (including end sills) shall be furnished. Stub crossmembers, as required at wheel housing to provide required strength, shall be furnished. Flooring with integrally formed cross members meet these requirements.

Roof shall be one piece or shall have a one piece center section with caps at the front, rear and sides, not less than 1 mm (0.040 in) thick aluminum. Rain gutters shall be provided over all doors. All body seams and joints shall be dust and weather sealed. Side panel shall be protected with OEM protective rub rails.

An all metal aluminum floor shall be provided with safety tread that shall be not less than 0.125 in., except for the driver's area and steps which shall be not less than 18 gage (1.2 mm (0.0478 in)). Floor and support members shall sustain an evenly distributed load of 610 kg per sq m (125 lb per sq ft) of floor area. Alternate floor construction shall be of extruded aluminum, dry freight construction with strength at least equal to that of steel.

The entire roof and sides shall be lined and completely insulated with no less than 2.5 cm (1 in) thick fiberglass batting or polystyrene. Exterior doors shall be lined on inside or double paneled. Headliner for roof and side lining shall be sheet aluminum min/1mm (0.04in), or 6.4 mm (0.25 in) thick minimum exterior grade plywood. The interior body sides shall be smooth or ribbed with no other protrusions except fasteners and corner posts. The fasteners shall project not more than 2.8 mm (0.11 in) into the interior and shall be blended and smooth. Side lining panels furnished shall completely line the body without gaps between panels, except at roof line, where a gap between side and roof panels shall not exceed 1.3 cm (0.5 in). All interior panels shall be removable to facilitate body repair. Each sheet metal headliner and side lining panel shall be rigid, shall have no sharp edges exposed to the touch and shall be fastened so as to prevent scalloping and, edge ridges in the panels. Each wood headliner and sidelining panel shall be free of defects, sanded smooth and flush with adjacent panels. Dimensions (with side panels installed) shall be as specified. The body side lining (panels) shall be furnished reinforced for load support and with tie rings. The recessed tie rings shall be spaced on 61 cm (24 in) centers and 76 cm (30 in) above floor line, measured to center of tie ring + or - 5 cm (2 in). Tie rings are not required on bulkhead.

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 9201 LBS GVWR

This single rear wheel, forward-control, walk-in style vehicle shall have an integral driver's compartment and enclosed body and as specified. Multistop Van Trucks require a solid type interior partition (DPB) when AC is specified. This is done to insure that the passenger compartment of this vehicle will be adequately cooled. Selecting a screen type interior partition (DPA) or no partition with AC will result in severe performance degradation of the air conditioning in the passenger compartment. The equipment listed below shall be the minimum furnished on this vehicle.

White is the standard color for this item. If a color other than white is desired, option "BPC" Body Paint Color must be ordered. Ordering option BPC requires that a color be chosen from the "Quantity and Color Selections" page in AUTOCHOICE.

| | |
|---|----------------------|
| Body Load Length, m (ft): | 3.0 (10) |
| Body Load Height:, m (ft): | 1.8 (6) |
| Body Interior Capacity Min, m3 (ft3): | 10 (350) |
| Cargo Door Type: | Center Panel Door(s) |
| Reinforced Body Inside Lining & Tiedowns: | 2 Sides |

Item # 131

| GSA COMPONENTS | GSA. MIN. REQ. | NORTHSIDE FORD |
|--|----------------------------|----------------|
| BODY/CHASSIS | | E350 |
| MFG. MODEL CODE | | E-39 |
| PAYLOAD min. kg. (lbs.) | 1542 (3400) | 3624 |
| GROSS VEHICLE WEIGHT RATING min./max. kg (lbs.) | 4174 (9201) / 4535 (10000) | 9600 |
| WHEEL BASE cm. (in.) | 351 (138) | 138 |
| ENGINE MINIMUMS | | |
| ENGINE TYPE (Cylinder/Liter) | 8 / 5.4 | 8/5.4 |
| HORSEPOWER (min) | 255 | 255 |
| TORQUE (ft.-lb.) | 350 | 350 |
| COOLING SYSTEM | HDA | comply |
| TRANSMISSION | | |
| AUTOMATIC TRANSMISSION | 5 sp w/ OD w/ HDA Cooling | 5 sp w/OD |
| ELECTRICAL | | |
| ALTERNATOR min. (Amps) | 115 | 115 |
| BATTERY min. (CCA) | 600 | 650 |
| FUEL | | |
| FUEL CAPACITY min. Liters (gals.) | 130 (35) | 37 |
| EXTERIOR | | |
| REAR VIEW MIRRORS | Combination | comply |
| DOORS AND WINDOWS | | |
| DOORS | 1 | comply |
| KEYED DOOR LOCKS | Req | left and right |
| WIPERS-WINDSHIELD-INTERMITTENT | Req | comply |
| INTERIOR | | |
| POWER STEERING | Req | comply |
| UPHOLSTERY | Vinyl | comply |
| FLOOR | | |
| FLOOR COVERING | Vinyl in cab only | comply |
| RADIO | | |
| RADIO | AM /FM | comply |
| SEATS | | |
| SEATING CAPACITY min. | 2 | 2 |
| SAFETY | | |
| POWER ANTILOCK BRAKES, FRONT AND REAR RESTRAINT SYSTEM, DRIVER AND PASSENGER | Req | comply |
| SUPPLEMENTAL RESTRAINT SYSTEM, DRIVER & FRONT PASSENGER | Req | comply |
| SUSPENSION | | |
| SUSPENSION/SHOCKS | HDA | comply |
| TIRES AND WHEELS | | |
| WHEEL DIAMETER | 16 | 16 |

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 9201 LBS GVWR

Item # 131

| GSA COMPONENTS VENDOR INSTALLED BODY OPTIONS | GSA. MIN. REQ. | NORTHSIDE FORD E350 |
|--|------------------------|------------------------|
| TIRES STEP TYPE REAR BUMPER w/ RH2 PROVISIONS | LT 245/R/hwy-AS Req | LT 245/R/AS comply |
| WARRANTY | | |
| MFG STANDARD WARRANTY | 3 yr /36000 miles | comply |
| VENDOR BODY WARRANTY | 1 yr / 12000 miles | comply |

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 9201 LBS GVWR

Item # 131 - OPTIONAL EQUIPMENT

| | | NORTHSIDE FORD |
|--------------------------------------|---|-------------------------------|
| ENGINES | | E350 |
| E5 | UPGRADED EXTRA POWER V8/V10 ENGINE Eng-Cyl/HP/Torque | Stand Alone 10/6.8,305,420 |
| ENGINE ACCESSORY OPTIONS | | |
| EH | ENGINE BLOCK HEATER | Stand Alone |
| INTERIOR | | |
| CRTS | CRUISE CONTROL AND TILT STEERING | N/A |
| SK | METRIC ODOMETER | Stand Alone |
| AC | AIR CONDITIONING | Package |
| CU | CLOTH UPHOLSTERY | Stand Alone |
| RADIO | | |
| RACS | AM/FM RADIO WITH CASSETTE PLAYER | Stand Alone |
| RAD | AM/FM RADIO WITH COMPACT DISC PLAYER | Stand Alone |
| TIRES AND WHEELS | | |
| TD | DELETE SPARE TIRE ASSEMBLY | Stand Alone |
| VENDOR INSTALLED BODY OPTIONS | | |
| BPC | BODY PAINT COLOR | Stand Alone |
| BR | TRANSLUCENT ROOF | Stand Alone |
| BUAV | BACK-UP ALARM | Stand Alone |
| CMS | CROSSVIEW MIRROR SYSTEM | Stand Alone |
| DPA | INTERIOR PARTITION, SCREEN TYPE | Stand Alone |
| DPB | INTERIOR PARTITION, SOLID TYPE | Stand Alone |
| DPW | PARTITION DOOR WINDOW | Package |
| DVC | ROLL-UP REAR DOOR | Stand Alone |
| DVD | FULL WIDTH DUAL REAR DOORS | Stand Alone |
| DVF | WOOD FLOORING | Stand Alone |
| DVG | DRIVER'S FAN | Stand Alone |
| HTGR | RAIL TYPE LIFT GATE | Package |
| HTP | POWER CLOSE LIFT GATE | Package |
| J560 | SAE J560 TRACTOR-TRAILER ELECTRICAL | Stand Alone |
| RH3V | DRAW BAR RECIEVER CLASS III | Stand Alone |
| RH4V | DRAW BAR RECIEVER CLASS IV | N/A |
| VRS | ROOF VENTILATION, STATIC | Stand Alone |
| DELIVERY | | |
| 1611 | OEM EXPORT DOCUMENT FEE | Stand Alone |
| CNS | CONSIGNEE DELIVERY (NO DEALER PREP) | Stand Alone |
| DDRH | DEALER DELIVERY HAWAII | N/A |
| DDRP | DEALER DELIVERY PUERTO RICO | N/A |
| MISCELLANEOUS | | |
| MIL | DATA PLATES OR DD250 | Stand Alone |
| PSM | PARTS AND SERVICE MANUALS | Stand Alone |
| PSME | PARTS AND SERVICE MANUALS -- ELECTRONIC | N/A |

S=Standard SA=Stand Alone PKG=Package (includes, requires or excludes other options) NA=Not Available

THIS PAGE HAS BEEN INTENTIONALLY LEFT BLANK

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 10,001 LBS GVWR

This forward-control, walk-in style vehicle shall have an integral driver's compartment and enclosed body and as specified. Multistop Van Trucks require a solid type interior partition (DPB) when AC is specified. This is done to insure that the passenger compartment of this vehicle will be adequately cooled. Selecting a screen type interior partition (DPA) or no partition with AC will result in severe performance degradation of the air conditioning in the passenger compartment. The equipment listed below shall be the minimum furnished on this vehicle.

White is the standard color for this item. If a color other than white is desired, option "BPC" Body Paint Color must be ordered. Ordering option BPC requires that a color be chosen from the "Quantity and Color Selections" page in AUTOCHOICE.

| | |
|---|----------------------|
| Body Load Length, m (ft): | 3.6 (12) |
| Body Load Height:, m (ft): | 1.8 (6) |
| Body Interior Capacity Min, m ³ (ft3): | 13 (450) |
| Cargo Door Type: | Center Panel Door(s) |
| Reinforced Body Inside Lining & Tiedowns: | 2 Sides |

Item # 134

| GSA COMPONENTS | GSA. MIN. REQ. | NORTHSIDE FORD | WORKHORSE CUSTOM CHASSIS |
|--|-----------------------------|----------------------------|--------------------------|
| BODY/CHASSIS | | E350 | P42 |
| MFG. MODEL CODE | | E-39 | WP31442 |
| PAYLOAD min. kg. (lbs.) | 2155 (4700) | 4813 | 2155 (4700) |
| GROSS VEHICLE WEIGHT RATING min./max. kg (lbs.) | 4536 (10001) / 6350 (14000) | 11000 | 11000 (4989) |
| ENGINE MINIMUMS | | | |
| ENGINE TYPE (Cylinder/Liter) | 8 / 4.8 | 8/5.4 | 8/4.8 |
| HORSEPOWER (min) | 255 | 255 | 270 |
| TORQUE (ft.-lb.) | 350 | 350 | 285 |
| COOLING SYSTEM | HDA | comply | HDA |
| TRANSMISSION | | | |
| AUTOMATIC TRANSMISSION | 4 sp w/ OD w/ HDA Cooling | 4 speed w/OD | 4SP w/OD w/HDA Cooling |
| ELECTRICAL | | | |
| ALTERNATOR min. (Amps) | 130 | 130 | 145 |
| BATTERY min. (CCA) | 600 | 600 | 690 |
| FUEL | | | |
| FUEL CAPACITY min. Liters (gals.) | 130 (35) | 35 | 148/40 |
| EXTERIOR | | | |
| REAR VIEW MIRRORS | Combination | comply | comply |
| DOORS AND WINDOWS | | | |
| DOORS | 1 | n/a | 2 |
| KEYED DOOR LOCKS | Req | left and right | left and right |
| WIPERS-WINDSHIELD-INTERMITTENT | Req | comply | comply |
| INTERIOR | | | |
| POWER STEERING | Req | comply | comply |
| UPHOLSTERY | Vinyl | comply | comply |
| FLOOR | | | |
| FLOOR COVERING | Vinyl in cab only | comply | comply |
| RADIO | | | |
| RADIO | AM /FM | AM/FM w/clock | comply |
| SEATS | | | |
| SEATING CAPACITY min. | 2 | 2 | 2 |
| SAFETY | | | |
| POWER ANTILOCK BRAKES, FRONT AND REAR RESTRAINT SYSTEM, DRIVER AND PASSENGER SUPPLEMENTAL RESTRAINT SYSTEM, DRIVER & FRONT PASSENGER | Req Req Req | comply comply comply | comply comply N/A |
| SUSPENSION | | | |
| SUSPENSION/SHOCKS | HDA | comply | HDA |

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 10,001 LBS GVWR

Item # 134

| GSA COMPONENTS | GSA. MIN. REQ. | NORTHSIDE FORD | WORKHORSE CUSTOM CHASSIS |
|---|-----------------------|-----------------------|---------------------------------|
| TIRES AND WHEELS | | E350 | P42 |
| WHEEL DIAMETER | 16 Duals | 16 | 16 duals |
| TIRES | LT 215/R/hwy-AS | LT 225/R/AS | LT 245/R/hwy |
| VENDOR INSTALLED BODY OPTIONS | | | |
| STEP TYPE REAR BUMPER w/ RH2 PROVISIONS | Req | comply | comply |
| WARRANTY | | | |
| MFG STANDARD WARRANTY | 3 yr / 36000 miles | comply | comply |
| VENDOR BODY WARRANTY | 1 yr / 12000 miles | comply | comply |

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 10,001 LBS GVWR

Item # 134 - OPTIONAL EQUIPMENT

| | | NORTHSIDE FORD | WORKHORSE CUSTOM |
|--------------------------------------|---|-------------------------------|--------------------------|
| BODY/CHASSIS | | E350 | P42 |
| GU | GVWR REDUCTION | N/A | N/A |
| ENGINES | | | |
| E5 | UPGRADED EXTRA POWER V8/V10 ENGINE Eng-Cyl/HP/Torque | Stand Alone 10/6.8,305,420 | N/A |
| YD | DIESEL ENGINE Eng-Cyl/HP/Torque | N/A | Package 4/5.2,190,387 |
| ENGINE ACCESSORY OPTIONS | | | |
| OLS | Oil Life System | N/A | N/A |
| EH | ENGINE BLOCK HEATER | Stand Alone | Stand Alone |
| DRIVE AXLE | | | |
| D3 | SPECIAL TRACTION DIFFERENTIAL | Stand Alone | N/A |
| D7 | TOWING/MOUNTAIN RATIO | Stand Alone | Stand Alone |
| INTERIOR | | | |
| CRTS | CRUISE CONTROL AND TILT STEERING | N/A | Standard |
| SK | METRIC ODOMETER | Stand Alone | Stand Alone |
| AC | AIR CONDITIONING | Package | Package |
| CU | CLOTH UPHOLSTERY | Stand Alone | Stand Alone |
| RADIO | | | |
| RACS | AM/FM RADIO WITH CASSETTE PLAYER | Stand Alone | Stand Alone |
| RAD | AM/FM RADIO WITH COMPACT DISC PLAYER | Stand Alone | Package |
| TIRES AND WHEELS | | | |
| TD | DELETE SPARE TIRE ASSEMBLY | Stand Alone | Stand Alone |
| TT | TRACTION TREAD--REAR TIRES ONLY | N/A | Stand Alone |
| VENDOR INSTALLED BODY OPTIONS | | | |
| BPC | BODY PAINT COLOR | Stand Alone | Stand Alone |
| BR | TRANSLUCENT ROOF | Stand Alone | Stand Alone |
| BUAV | BACK-UP ALARM | Stand Alone | Stand Alone |
| CMS | CROSSVIEW MIRROR SYSTEM | Stand Alone | Stand Alone |
| DPA | INTERIOR PARTITION, SCREEN TYPE | Stand Alone | Stand Alone |
| DPB | INTERIOR PARTITION, SOLID TYPE | Package | Stand Alone |
| DPW | PARTITION DOOR WINDOW | Stand Alone | Package |
| DV4 | CARGO BODY LENGTH 4.3M (14 FT) | Stand Alone | Stand Alone |
| DV6 | CARGO BODY LENGTH 4.9 M (16 FT) | Stand Alone | Stand Alone |
| DVC | ROLL-UP REAR DOOR | Stand Alone | Stand Alone |
| DVD | FULL WIDTH DUAL REAR DOORS | Stand Alone | Stand Alone |
| DVE | EXTRA HEIGHT INTERIOR, MIN. 203 CM | Stand Alone | Stand Alone |
| DVE1 | EXTRA HEIGHT INTERIOR, MIN. 213 CM | Stand Alone | Stand Alone |
| DVF | WOOD FLOORING | Stand Alone | Stand Alone |
| DVG | DRIVER'S FAN | Stand Alone | Stand Alone |
| HTGR | RAIL TYPE LIFT GATE | Package | |
| HTP | POWER CLOSE LIFT GATE | Package | |
| J560 | SAE J560 TRACTOR-TRAILER ELECTRICAL | Stand Alone | |
| RH3V | DRAW BAR RECIEVER CLASS III | Stand Alone | |
| RH4V | DRAW BAR RECIEVER CLASS IV | N/A | |
| VRS | ROOF VENTILATION, STATIC | Stand Alone | |
| DELIVERY | | | |
| 1611 | OEM EXPORT DOCUMENT FEE | Stand Alone | |
| CNS | CONSIGNEE DELIVERY (NO DEALER PREP) | Stand Alone | |
| DDRH | DEALER DELIVERY HAWAII | N/A | |
| DDRP | DEALER DELIVERY PUERTO RICO | N/A | |
| MISCELLANEOUS | | | |
| MIL | DATA PLATES OR DD250 | Stand Alone | |
| PSM | PARTS AND SERVICE MANUALS | Stand Alone | |
| PSME | PARTS AND SERVICE MANUALS -- ELECTRONIC | N/A | |

S=Standard

SA=Stand Alone

PKG=Package (includes, requires or excludes other options)

NA=Not Available

THIS PAGE HAS BEEN INTENTIONALLY LEFT BLANK

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 14,001 LBS GVWR

This forward-control, walk-in style vehicle shall have an integral driver's compartment and enclosed body and as specified. Multistop Van Trucks require a solid type interior partition (DPB) when AC is specified. This is done to insure that the passenger compartment of this vehicle will be adequately cooled. Selecting a screen type interior partition (DPA) or no partition with AC will result in severe performance degradation of the air conditioning in the passenger compartment. The equipment listed below shall be the minimum furnished on this vehicle.

White is the standard color for this item. If a color other than white is desired, option "BPC" Body Paint Color must be ordered. Ordering option BPC requires that a color be chosen from the "Quantity and Color Selections" page in AUTOCHOICE.

| | |
|---|----------------------|
| Body Load Length, m (ft): | 4.3 (14) |
| Body Load Height:, m (ft): | 1.8 (6) |
| Body Interior Capacity Min, m3 (ft3): | 15 (550) |
| Cargo Door Type: | Center Panel Door(s) |
| Reinforced Body Inside Lining & Tiedowns: | 2 Sides |

Item # 134B

| GSA COMPONENTS | GSA. MIN. REQ. | ENGLAND FORD | FREIGHTLINER | WORKHORSE CUSTOM CHASSIS |
|--|-----------------------------|----------------|--------------------------|--------------------------|
| BODY/CHASSIS | | E450 | MT-45 | P42 |
| MFG. MODEL CODE | | E-49 | MT45 | WP31842 |
| PAYLOAD min. kg. (lbs.) | 3175 (7000) | 7365 | 7000 | 3175 (7000) |
| GROSS VEHICLE WEIGHT RATING min./max. kg (lbs.) | 6351 (14001) / 7257 (16000) | 14050 | 16000 | 6395 (14100) |
| WHEEL BASE cm. (in.) | 401 (158) | 158 | | 157 |
| ENGINE MINIMUMS | | | | |
| ENGINE TYPE (Cylinder/Liter) | 6 / 4.8 | 8/5.4 | 6/5.9 | 8/4.8 |
| HORSEPOWER (min) | 185 | 255 | 185 | 270 |
| TORQUE (ft.-lb.) | 285 | 350 | 420 | 285 |
| COOLING SYSTEM | HDA | comply | HDA | HDA |
| TRANSMISSION | | | | |
| AUTOMATIC TRANSMISSION | 4 sp w/ OD w/ HDA Cooling | 5 spd w/OD | 5 spd w/OD w/HDA cooling | 4 spd w/OD w/HDA cooling |
| ELECTRICAL | | | | |
| ALTERNATOR min. (Amps) | 115 | 115 | 130 | 145 |
| BATTERY min. (CCA) | 600 | 650 | 1300 | 690 |
| FUEL | | | | |
| FUEL CAPACITY min. Liters (gals.) | 130 (35) | 55 | 170 (45) | 148/40 |
| EXTERIOR | | | | |
| REAR VIEW MIRRORS | Combination | n/a | n/a | n/a |
| DOORS AND WINDOWS | | | | |
| DOORS | 1 | comply | comply | comply |
| KEYED DOOR LOCKS | Req | left and right | left and right | left and right |
| WIPERS-WINDSHIELD-INTERMITTENT | Req | comply | comply | comply |
| INTERIOR | | | | |
| POWER STEERING | Req | comply | power steering | comply |
| UPHOLSTERY | Vinyl | comply | comply | comply |
| FLOOR | | | | |
| FLOOR COVERING | Vinyl in cab only | comply | comply | comply |
| RADIO | | | | |
| RADIO | AM /FM | comply | comply | comply |
| SEATS | | | | |
| SEATING CAPACITY min. | 2 | comply | comply | comply |
| SAFETY | | | | |
| POWER ANTILOCK BRAKES, FRONT AND REAR | Req | comply | comply | comply |
| RESTRAINT SYSTEM, DRIVER AND PASSENGER | Req | comply | comply | comply |
| SUPPLEMENTAL RESTRAINT SYSTEM, DRIVER & FRONT PASSENGER | Req | comply | comply | comply |

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 14,001 LBS GVWR

Item # 134B

| GSA COMPONENTS | GSA. MIN. REQ. | ENGLAND FORD | FREIGHTLINER | WORKHORSE CUSTOM CHASSIS |
|---|---------------------|--------------|------------------------------------|--------------------------|
| SUSPENSION | | E450 | MT-45 | P42 |
| SUSPENSION/SHOCKS | HDA | comply | HDA | HDA |
| TIRES AND WHEELS | | | | |
| WHEEL DIAMETER | 19.5 Duals | 16 | 19.5 Duals | 19.5 Duals |
| TIRES | AP 225/70/R/RS | LT225/R/AS | AP 225/70/R/RS | 800R 19.5E hwy |
| VENDOR INSTALLED BODY OPTIONS | | | | |
| STEP TYPE REAR BUMPER w/ RH2 PROVISIONS | Req | comply | step type rear bumper w/rh2provisi | comply |
| WARRANTY | | | | |
| MFG STANDARD WARRANTY | 3 yrs / 36000 miles | comply | 3 yrs / 36000 miles | comply |
| VENDOR BODY WARRANTY | 1 yr / 12000 miles | comply | 3 yrs / 36000 miles | comply |

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 14,001 LBS GVWR

Item # 134B - OPTIONAL EQUIPMENT

| | | ENGLAND FORD | FREIGHTLINER | WORKHORSE CUSTOM CHASSIS |
|--------------------------------------|---|-------------------------------|--------------|------------------------------|
| | | E450 | MT-45 | P42 |
| ENGINES | | | | |
| E5 | UPGRADED EXTRA POWER V8/V10 ENGINE Eng-Cyl/HP/Torque | Stand Alone 10/6.8,305,420 | N/A | Stand Alone 8/6.0,300,355 |
| YD | DIESEL ENGINE Eng-Cyl/HP/Torque | N/A N/A,N/A,N/A | Standard | Package 4/5.2,190,387 |
| ENGINE ACCESSORY OPTIONS | | | | |
| EH | ENGINE BLOCK HEATER | Stand Alone | Package | Stand Alone |
| DRIVE AXLE | | | | |
| D7 | TOWING/MOUNTAIN RATIO | Stand Alone | Stand Alone | Stand Alone |
| INTERIOR | | | | |
| CRTS | CRUISE CONTROL AND TILT STEERING | Stand Alone | Stand Alone | Standard |
| SK | METRIC ODOMETER | Stand Alone | Stand Alone | Stand Alone |
| AC | AIR CONDITIONING | Package | Package | Package |
| CJ | CLOTH UPHOLSTERY | Stand Alone | Stand Alone | Stand Alone |
| RADIO | | | | |
| RACS | AM/FM RADIO WITH CASSETTE PLAYER | Stand Alone | Standard | Stand Alone |
| RAD | AM/FM RADIO WITH COMPACT DISC PLAYER | Stand Alone | Stand Alone | Package |
| TIRES AND WHEELS | | | | |
| TD | DELETE SPARE TIRE ASSEMBLY | Stand Alone | Stand Alone | Stand Alone |
| TT | TRACTION TREAD--REAR TIRES ONLY | N/A | Stand Alone | Stand Alone |
| VENDOR INSTALLED BODY OPTIONS | | | | |
| BPC | BODY PAINT COLOR | Stand Alone | Stand Alone | Stand Alone |
| BR | TRANSLUCENT ROOF | Stand Alone | Stand Alone | Standard |
| BUAV | BACK-UP ALARM | Stand Alone | Stand Alone | Stand Alone |
| CMS | CROSSVIEW MIRROR SYSTEM | Stand Alone | Stand Alone | Stand Alone |
| DPA | INTERIOR PARTITION, SCREEN TYPE | Stand Alone | Stand Alone | Stand Alone |
| DPB | INTERIOR PARTITION, SOLID TYPE | Stand Alone | Stand Alone | Stand Alone |
| DPW | PARTITION DOOR WINDOW | Stand Alone | Package | Package |
| DV6 | CARGO BODY LENGTH 4.9 M (16 FT) | Stand Alone | Stand Alone | Stand Alone |
| DV8 | CARGO BODY LENGTH 5.5 M (18 FT) | Stand Alone | Stand Alone | Package |
| DVC | ROLL-UP REAR DOOR | Stand Alone | Stand Alone | Stand Alone |
| DVD | FULL WIDTH DUAL REAR DOORS | Stand Alone | Stand Alone | Stand Alone |
| DVE | EXTRA HEIGHT INTERIOR, MIN. 203 CM | Stand Alone | Stand Alone | Stand Alone |
| DVE1 | EXTRA HEIGHT INTERIOR, MIN. 213 CM | Stand Alone | Stand Alone | Stand Alone |
| DVF | WOOD FLOORING | Stand Alone | Stand Alone | Stand Alone |
| DVG | DRIVER'S FAN | Stand Alone | Stand Alone | Stand Alone |
| HTGR | RAIL TYPE LIFT GATE | Stand Alone | Stand Alone | Stand Alone |
| HTP | POWER CLOSE LIFT GATE | Stand Alone | Package | Package |
| J560 | SAE J560 TRACTOR-TRAILER ELECTRICAL | Stand Alone | Stand Alone | Stand Alone |
| RH3V | DRAW BAR RECIEVER CLASS III | Stand Alone | Stand Alone | Package |
| RH4V | DRAW BAR RECIEVER CLASS IV | Stand Alone | Stand Alone | Package |
| VRS | ROOF VENTILATION, STATIC | Stand Alone | Stand Alone | Stand Alone |
| DELIVERY | | | | |
| 1611 | OEM EXPORT DOCUMENT FEE | Stand Alone | N/A | Stand Alone |
| CNS | CONSIGNEE DELIVERY (NO DEALER PREP) | Stand Alone | Stand Alone | Stand Alone |
| DDRH | DEALER DELIVERY HAWAII | N/A | N/A | Stand Alone |
| DDRP | DEALER DELIVERY PUERTO RICO | N/A | N/A | Stand Alone |
| MISCELLANEOUS | | | | |
| MIL | DATA PLATES OR DD250 | Stand Alone | Stand Alone | Stand Alone |
| PSM | PARTS AND SERVICE MANUALS | Stand Alone | Stand Alone | Stand Alone |
| PSME | PARTS AND SERVICE MANUALS -- ELECTRONIC | Stand Alone | Stand Alone | Stand Alone |

S=Standard

SA=Stand Alone

PKG=Package (includes, requires or excludes other options)

NA=Not Available

THIS PAGE HAS BEEN INTENTIONALLY LEFT BLANK

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 16,0001 LBS GVWR

This forward-control, walk-in style vehicle shall have an integral driver's compartment and enclosed body and as specified. Multistop Van Trucks require a solid type interior partition (DPB) when AC is specified. This is done to insure that the passenger compartment of this vehicle will be adequately cooled. Selecting a screen type interior partition (DPA) or no partition with AC will result in severe performance degradation of the air conditioning in the passenger compartment. The equipment listed below shall be the minimum furnished on this vehicle.

White is the standard color for this item. If a color other than white is desired, option "BPC" Body Paint Color must be ordered. Ordering option BPC requires that a color be chosen from the "Quantity and Color Selections" page in AUTOCHOICE.

Body Load Length, m (ft): 4.8 (16)
 Body Load Height:, m (ft): 1.8 (6)
 Body Interior Capacity Min, m3 (ft3): 18 (660)
 Cargo Door Type: Center Panel Door(s)
 Reinforced Body Inside Lining & Tiedowns: 2 Sides

Item # 134F

| GSA COMPONENTS | GSA. MIN. REQ. | FREIGHTLINER | WORKHORSE CUSTOM CHASSIS |
|---|-----------------------------|--------------------------------------|--------------------------|
| BODY/CHASSIS | | MT-45 | W52 |
| MFG. MODEL CODE | | MT45 | WP31952 |
| PAYLOAD min. kg. (lbs.) | 4535 (10000) | 10000 | 4535 (10000) |
| GROSS VEHICLE WEIGHT RATING min./max. kg (lbs.) | 7258 (16001) / 8845 (19500) | 19000 | 8845 (19500) |
| ENGINE MINIMUMS | | | |
| ENGINE TYPE (Cylinder/Liter) | 6 / 5.9 | 6 / 5.9 | 8/8.1 |
| HORSEPOWER (min) | 185 | 185 | 340 |
| TORQUE (ft.-lb.) | 420 | 420 | 455 |
| COOLING SYSTEM | HDA | hda | HDA |
| ELECTRICAL | | | |
| ALTERNATOR min. (Amps) | 130 | 130 | 145 |
| BATTERY min. (CCA) | 600 | 1300 | 690 |
| FUEL | | | |
| FUEL CAPACITY min. Liters (gals.) | 130 (35) | 170 (45) | 148/40 |
| EXTERIOR | | | |
| REAR VIEW MIRRORS | Combination | comply | comply |
| DOORS AND WINDOWS | | | |
| DOORS | 1 | 2 | 2 |
| KEYED DOOR LOCKS | | left and right | left and right |
| WIPERS-WINDSHIELD-INTERMITTENT | | wipers-windshield-intermittent | comply |
| INTERIOR | | | |
| POWER STEERING | | power steering | comply |
| UPHOLSTERY | Vinyl | vinyl | comply |
| FLOOR | | | |
| FLOOR COVERING | Vinyl in cab only | comply | comply |
| SAFETY | | | |
| POWER ANTILOCK BRAKES, FRONT AND REAR | Req | power antilock brakes front and rear | comply |
| RESTRAINT SYSTEM, DRIVER AND PASSENGER | Req | restraint driver and passenger | comply |
| SUPPLEMENTAL RESTRAINT SYSTEM, DRIVER & FRONT PASSENGER | Req | none | n/a |
| SUSPENSION | | | |
| SUSPENSION/SHOCKS | HDA | HDA | HDA |
| TIRES AND WHEELS | | | |
| WHEEL DIAMETER | 19.5 Duals | 19.5 Duals | 19.5 duals |
| TIRES | Commercial 225 /R/RS | Commercial 225 /R/RS | Commercial 225/R/ |
| VENDOR INSTALLED BODY OPTIONS | | | |
| STEP TYPE REAR BUMPER w/ RH2 PROVISIONS | Req | step type rear bumper w/rh2 prov | comply |
| WARRANTY | | | |
| MFG STANDARD WARRANTY | 3 yrs / 36000 miles | 3 yrs / 36000 miles | 3 yrs / 36000 miles |
| VENDOR BODY WARRANTY | 1 yr / 12000 miles | 3 yrs / 36000 miles | 3 yrs / 36000 miles |

TABLE 26 - CONTINUED

4 X 2 MULTISTOP VAN, MIN 16,0001 LBS GVWR

Item # 134F - OPTIONAL EQUIPMENT

| | | FREIGHTLINER | WORKHORSE CUSTOM CHASSIS |
|--------------------------------------|---|--------------|---------------------------|
| | | MT-45 | W52 |
| ENGINES | | | |
| E5 | UPGRADED EXTRA POWER V8/V10 ENGINE Eng-Cyl/HP/Torque | N/A | Standard 8/8.1,340,455 |
| YD | DIESEL ENGINE Eng-Cyl/HP/Torque | Standard | N/A |
| ENGINE ACCESSORY OPTIONS | | | |
| OLS | Oil Life System | N/A | N/A |
| EH | ENGINE BLOCK HEATER | Package | Stand Alone |
| DRIVE AXLE | | | |
| D7 | TOWING/MOUNTAIN RATIO | Stand Alone | N/A |
| INTERIOR | | | |
| CRTS | CRUISE CONTROL AND TILT STEERING | Stand Alone | Standard |
| SK | METRIC ODOMETER | Stand Alone | Stand Alone |
| AC | AIR CONDITIONING | Package | Package |
| CU | CLOTH UPHOLSTERY | Stand Alone | Stand Alone |
| RADIO | | | |
| RACS | AM/FM RADIO WITH CASSETTE PLAYER | Standard | Stand Alone |
| RAD | AM/FM RADIO WITH COMPACT DISC PLAYER | Stand Alone | Package |
| TIRES AND WHEELS | | | |
| TD | DELETE SPARE TIRE ASSEMBLY | Stand Alone | Stand Alone |
| TT | TRACTION TREAD--REAR TIRES ONLY | Stand Alone | Stand Alone |
| VENDOR INSTALLED BODY OPTIONS | | | |
| BPC | BODY PAINT COLOR | Stand Alone | Stand Alone |
| BR | TRANSLUCENT ROOF | Stand Alone | Standard |
| BUAV | BACK-UP ALARM | Stand Alone | Stand Alone |
| CMS | CROSSVIEW MIRROR SYSTEM | Stand Alone | Stand Alone |
| DPA | INTERIOR PARTITION, SCREEN TYPE | Stand Alone | Stand Alone |
| DPB | INTERIOR PARTITION, SOLID TYPE | Stand Alone | Stand Alone |
| DPW | PARTITION DOOR WINDOW | Package | Package |
| DV4 | CARGO BODY LENGTH 4.3M (14 FT) | Stand Alone | N/A |
| DV8 | CARGO BODY LENGTH 5.5 M (18 FT) | Stand Alone | Standard |
| DVC | ROLL-UP REAR DOOR | Stand Alone | Stand Alone |
| DVD | FULL WIDTH DUAL REAR DOORS | Stand Alone | Stand Alone |
| DVE | EXTRA HEIGHT INTERIOR, MIN. 203 CM | Stand Alone | Stand Alone |
| DVE1 | EXTRA HEIGHT INTERIOR, MIN. 213 CM | Stand Alone | Stand Alone |
| DVF | WOOD FLOORING | Stand Alone | Stand Alone |
| DVG | DRIVER'S FAN | Stand Alone | Stand Alone |
| HTGR | RAIL TYPE LIFT GATE | Stand Alone | Stand Alone |
| HTP | POWER CLOSE LIFT GATE | Package | Package |
| J560 | SAE J560 TRACTOR-TRAILER ELECTRICAL | Stand Alone | Stand Alone |
| RH3V | DRAW BAR RECIEVER CLASS III | Stand Alone | Package |
| RH4V | DRAW BAR RECIEVER CLASS IV | N/A | Package |
| VRS | ROOF VENTILATION, STATIC | Stand Alone | Stand Alone |
| DELIVERY | | | |
| 1611 | OEM EXPORT DOCUMENT FEE | N/A | Stand Alone |
| CNS | CONSIGNEE DELIVERY (NO DEALER PREP) | Stand Alone | Stand Alone |
| DDRH | DEALER DELIVERY HAWAII | N/A | Stand Alone |
| DDRP | DEALER DELIVERY PUERTO RICO | N/A | Stand Alone |
| MISCELLANEOUS | | | |
| MIL | DATA PLATES OR DD250 | Stand Alone | Stand Alone |
| PSM | PARTS AND SERVICE MANUALS | Stand Alone | Stand Alone |
| PSME | PARTS AND SERVICE MANUALS -- ELECTRONIC | Stand Alone | Stand Alone |

S=Standard

SA=Stand Alone

PKG=Package (includes, requires or excludes other options)

NA=Not Available