

Table of Contents

I.	Introduction	
	Introduction	I-1
	Study Purpose	I-3
	Study Approach	I-3
	Internal Departmental Coordination	I-3
	Highway Cost Allocation Study	I-5
	Ongoing Truck Size and Weight Research Effort	I-6
	Public Outreach	I-6
	Study Presentation	I-6
	Overview	I-6
	Organization of Volume III	I-7
II.	Analytical Framework	
	Introduction	II-1
	Technical Foundation	II-1
	Illustrative Scenario Development	II-3
	Configurations	II-4
	Networks and Geographic Units	II-6
	National Network for Large Trucks	II-6
	National Highway System	II-6
	Analytical Networks for Longer Combination Vehicles	II-7
	Scenario Definitions	II-7
	Base Case	II-10
	Uniformity Scenario	II-11
	North American Trade Scenario	II-11
	Longer Combination Vehicles Nationwide Scenario	II-11
	H.R. 551 Scenario	II-12
	Triples Nationwide Scenario	II-12
	Impact Areas	II-12
	Freight Diversion	II-13
	Highway Agency Costs	II-13
	Pavement	II-13
	Bridge	II-14
	Roadway Geometry	II-14
	Safety	II-15
	Traffic Operations	II-16
	Environmental Quality and Energy Consumption	II-16
	Rail Impacts and Shipper Costs	II-17
III.	Scenario Descriptions	
	Introduction	III-1

Base Case	III-1
Introduction	III-1
Scenario Specifications	III-3
The Vehicles	III-4
The Networks	III-4
Access Provisions	III-4
Uniformity Scenario	III-4
Historical Perspective	III-6
Grandfather Provisions	III-6
Uniformity Legislation	III-7
Scenario Specifications	III-7
The Vehicles	III-7
The Network	III-9
Access Provisions	III-10
North American Trade Scenarios	III-10
Background: Policy Related Issues	III-11
North American Trade	III-11
International Container Traffic	III-11
Four-Axle Straight Trucks	III-14
Scenario Specifications	III-15
The Vehicles	III-15
The Network	III-16
Access Provisions	III-16
Longer Combination Vehicles Nationwide Scenario	III-16
Background: Vehicle Descriptions	III-19
Rocky Mountain Doubles	III-19
Turnpike Doubles	III-20
Triples	III-21
Scenario Description	III-22
The Vehicles	III-22
The Networks	III-22
Access Provisions	III-22
H. R. 551 Scenario	III-23
H.R. 551 Provisions and Background	III-23
Phase Out of Trailers Longer than 53 Feet	III-23
Termination of State Determination of Grandfather Rights	III-23
Freeze on National Highway System Weights	III-24
Scenario Specifications	III-24
The Vehicles	III-26
The Network	III-26
Access Provisions	III-27
Triples Nationwide Scenario	III-27
Scenario Specifications	III-27

The Vehicles	III-27
The Networks	III-27
Access Provisions	III-27

IV. Freight Distribution

Introduction	IV-1
Analytical Approach	IV-1
Rail and Truck Base Case Traffic	IV-1
Diversion	IV-3
Truck-to-Truck Diversion	IV-3
Rail-to-Truck Diversion	IV-5
Analytical Models	IV-7
Short-haul Truck Analysis	IV-7
Long-haul Truck and Rail Analysis	IV-8
Model Decision Making Process	IV-8
Input Data	IV-11
Weight Distribution	IV-15
Assessment of Scenario Impacts	IV-16
Uniformity Scenario	IV-16
North American Trade Scenarios	IV-19
44,000-pound Tridem Axle	IV-19
Truck-to-Truck Diversion	IV-19
Rail Carload-to-Truck Diversion	IV-21
Rail Intermodal-to-Truck Diversion	IV-21
51,000-pound Tridem Axle	IV-22
Truck-to-Truck Diversion	IV-23
Rail Carload-to-Truck Diversion	IV-24
Rail Intermodal-to-Truck Diversion	IV-24
Longer Combination Vehicles Nationwide Scenario	IV-24
Truck-to-truck Diversion	IV-26
Rail Carload-to-Truck Diversion	IV-27
Rail Intermodal-to-Truck Diversion	IV-28
H.R. 551 Scenario	IV-28
Triple-Trailer Combination Nationwide Scenario	IV-30
Truck-to-Truck Diversion	IV-32
Rail Carload-to-Truck Diversion	IV-33
Rail Intermodal-to-Truck Diversion	IV-33

V. Pavement

Introduction	V-1
Basic Principles	V-2
Truck-Pavement Interaction	V-2
Pavement Life Consumption	V-2

Analytical Approach	V-7
Tridem-axle Impact Research	V-7
The National Pavement Cost Model	V-11
Overview	V-11
Input Data	V-11
Pavement Deterioration Models	V-13
Cost Calculations	V-13
Assessment of Scenario Impacts	V-13
Uniformity Scenario	V-14
North American Trade Scenarios	V-14
Longer Combination Vehicles Nationwide Scenario	V-15
H.R. 551 Scenario	V-15
Triples Nationwide Scenario	V-15
VI. Bridge	
Introduction	VI-1
Basic Principles	VI-1
Truck-Bridge Interaction	VI-1
Bridge Impact Criteria	VI-3
Analytical Approach	VI-4
Overview	VI-5
Bridge Replacement	VI-8
Model Inputs	VI-8
Overstress Criteria	VI-8
Analytical Parameters	VI-9
Available Routes	VI-9
Specifications	VI-9
User Costs	VI-9
Assessment of Scenario Impacts	VI-11
VII. Roadway Geometry	
Introduction	VII-1
Basic Principles	VII-1
Truck Turning Characteristics	VII-1
Low-Speed Offtracking	VII-1
High-Speed Offtracking	VII-2
Roadway Geometry and Truck Operations	VII-3
Intersections	VII-3
Interchange Ramps	VII-3
Horizontal Curvature	VII-3
Analytical Approach	VII-3
Vehicle Offtracking Performance	VII-5
Impacts	VII-7

Geometric	VII-7
Staging Areas	VII-8
Costs	VII-9
Geometric Improvements	VII-9
Staging Areas	VII-9
Assessment of Scenario Impacts	VII-11
Uniformity Scenario	VII-13
North American Trade Scenarios	VII-13
Longer Combination Vehicles Nationwide Scenario	VII-13
H.R. 551 Scenario	VII-13
Triples Nationwide Scenario	VII-13
VIII. Safety	
Introduction	VIII-1
Larger and Heavier Truck Crash Patterns	VIII-1
Vehicle Stability and Control	VIII-6
Vehicle Stability	VIII-8
Steady-State Turn Induced Rollover	VIII-8
Evasive Maneuver-Induced Rollover	VIII-8
Vehicle Control	VIII-10
Comparison of Vehicle Stability and Control Performance	VIII-11
Assessment of Scenario Impacts	VIII-13
IX. Traffic Operations	
Introduction	IX-1
Basic Principles	IX-1
Traffic Congestion	IX-1
Other Traffic Effects	IX-1
Offtracking	IX-2
Passing or Being Passed on Two-Lane Roads	IX-4
Vehicle Acceleration	IX-4
Grades	IX-5
Industry Experience with Heavier Trucks	IX-6
Traction	IX-6
Lane Changing	IX-6
Intersection Requirements	IX-6
Analytical Approach	IX-7
Assessment of Scenario Impacts	IX-8
Uniformity Scenario	IX-9
North American Trade Scenarios	IX-9
Longer Combination Vehicles Nationwide Scenario	IX-9
H.R. 551 Scenario	IX-10
Triples Nationwide Scenario	IX-11

X.	Energy and Environment	
	Introduction	X-1
	Basic Principles	X-1
	Energy Consumption	X-1
	Air Quality	X-3
	Noise Emissions	X-3
	Analytical Approach	X-3
	Energy Consumption	X-3
	Air Quality	X-3
	Noise Emissions	X-4
	Assessment of Scenario Impacts	X-5
	Uniformity Scenario	X-5
	North American Trade Scenarios	X-5
	Longer Combination Vehicles Nationwide Scenario	X-6
	H.R. 551 Scenario	X-6
	Triples Nationwide Scenario	X-6
XI.	Rail	
	Introduction	XI-1
	Basic Principles	XI-2
	Overview of Class I Rail Industry	XI-2
	Financial Performance and Implications	XI-4
	Methodology	XI-4
	Study Caveats	XI-7
	Assessment of Scenario Impacts	XI-9
	Base Case	XI-9
	Uniformity Scenario	XI-10
	North American Trade Scenarios	XI-10
	44,000 Pound Tridem Axle	XI-11
	51,000 Pound Tridem Axle	XI-13
	Longer Combination Vehicles Nationwide Scenario	XI-13
	H.R. 551 Scenario	XI-16
	Triples Nationwide Scenario	XI-16
	Interpretation of Results	XI-18
	Railroad Response	XI-18
	Rate Increases Necessary to Replace Contribution	XI-18
	Erosion of Financial Strength	XI-19
XII.	Shipper Costs	
	Introduction	XII-1
	Basic Principles	XII-1
	Transportation Cost	XII-1
	Inventory Costs	XII-1

Relationship Between Transportation and Inventory Costs	XII-2
Analytical Approach	XII-2
Assessment of Scenario Impacts	XII-3
Uniformity Scenario	XII-3
North American Trade Scenario	XII-3
44,000-Pound Tridem Axle	XII-3
51,000-Pound Tridem axle	XII-3
Longer Combination Vehicles Nationwide Scenario	XII-4
H.R. 551 Scenario	XII-4
Triples Nationwide Scenario	XII-5

Appendix

Summary of Comments	A-1
---------------------------	-----

List of Tables

Table I-1. 2000 Federal Cost Responsibility and User Fees by Vehicle Class	I-7
Table III-1. Base Year and Forecast Commercial Vehicle Fleet and Travel	III-3
Table III-2. Current Use of Scenario Vehicles	III-5
Table III-3. Tridem Axle Weight Limits at Various Axle Spacings	III-13
Table III-4. Maximum Single and Tandem Axle Weight Limits – Canada, United States, Mexico	III-13
Table III-5. Container Port Traffic	III-14
Table III-6. International Standards Organization Container Capacity	III-15
Table III-7. States Routinely Allowing Semitrailers Longer Than 53 Feet	III-24
Table III-8. State Permitting of Overweight Loads – 1985-1995	III-25
Table V-1. Theoretical Load Equivalency Factors for Various Axle Groups and Loads for Major Types of Rigid and Flexible Pavement Distress	V-6
Table V-2. Theoretical Load Equivalency Factors for Scenario Vehicles	V-8
Table V-3. Theoretical Load Equivalency Factors Per 100,000 Pounds of Payload	V-9
Table V-4. Scenario Pavement Impacts	V-14
Table VI-1. Truck Configuration Parameters for Analysis of Bridge Impacts	VI-10
Table VI-2. Scenario Bridge Impacts	VI-12
Table VII-1. Offtracking Characteristics for Trucks Turning Right at Typical Two-Lane Roadway Intersection	VII-6
Table VII-2. Roadway Geometry Costs by Truck Configuration	VII-11
Table VII-3. Scenario Roadway Geometry Impacts	VII-12
Table VIII-1. Vehicle Descriptions and Specifications	VIII-13
Table VIII-2. Exposure Change Associated With Each Scenario	VIII-14
Table VIII-3. Comparison of Truck Use and Stability by Configuration	VIII-15
Table IX-1. Vehicle Passenger Car Equivalents on Rural Highways	IX-2

Table IX-2. Vehicle Passenger Car Equivalents on Urban Highways	IX-3
Table IX-3. Effects of Speed Differentials on Crash Involvement	IX-4
Table IX-4. Distribution of Grades on Arterial Highways	IX-5
Table IX-5. Traffic Operations Impacts of Truck Size and Weight Limits	IX-7
Table IX-6. Uniformity Scenario Traffic Impacts	IX-9
Table IX-7. North American Trade Scenarios Traffic Impacts	IX-10
Table IX-8. Longer Combinations Nationwide Scenario Traffic Impacts	IX-11
Table IX-9. H.R. 551 Scenario Traffic Impacts	IX-12
Table IX-10. Triples Nationwide Scenario Traffic Impacts	IX-13
Table X-1. Miles Per Gallon for Study Truck Configurations	X-2
Table X-2. Air Pollutant Emission Rates	X-2
Table X-3. Noise Passenger Car Equivalents for Trucks	X-4
Table X-4. Vehicle Miles of Travel by Configuration Under Uniformity Scenario	X-7
Table X-5. Energy and Environmental Impacts of Uniformity Scenario	X-7
Table X-6. Vehicle Miles of Travel by Configuration Under North American Trade Scenario, 51,000 Pound Tridem Axle Weight Limit	X-8
Table X-7. Energy and Environmental Impacts of North American Trade Scenario, 51,000 Pound Tridem Axle Limit	X-8
Table X-8. Vehicle Miles of Travel by Configuration for North American Trade Scenario, 44,000 Pound Tridem Axle Weight Limit	X-9
Table X-9. Energy and Environmental Impacts of North American Trade Scenario With 44,000 Pound Tridem Axle Weight Limit	X-9
Table X-10. Vehicle Miles of Travel by Configuration for Longer Combinations Nationwide Scenario	X-10
Table X-11. Energy and Environmental Impacts of Longer Combinations Nationwide Scenario	X-10
Table X-12. Vehicle Miles of Travel by Configuration Under H.R. 551 Scenario	X-11
Table X-13. Energy and Environmental Impacts of H.R. 551 Scenario	X-11
Table X-14. Vehicle Miles of Travel by Configuration for Triples Nationwide Scenario ..	X-12
Table X-15. Energy and Environmental Impacts of Triples Nationwide Scenario	X-12
Table XI-1. Industry and Railroad Cost Elasticities	XI-7
Table XI-2. Railroad Cost Studies	XI-9
Table XI-3. Revenues, Freight Service Expense, Contribution, and ROI for Base Case Scenario	XI-10
Table XI-4. Lost Revenues, Freight Service Expense, and Contribution for North American Trade Scenario With 44,000 Pound Tridem Axle	XI-11
Table XI-5. Car Miles, Freight Service Expense, Revenues from Operations, Contribution, and ROI for North American Trade Scenario With 44,000 Pound Tridem Axle	XI-12
Table XI-6. Lost Revenues, Freight Service Expense, and Contribution for North American Trade Scenario With 51,000 Pound Tridem Axle	XI-13
Table XI-7. Changes in Operational and Financial Indicators Under the North American Trade Scenario With 51,000 Pound Axles	XI-14
Table XI-8. Lost Revenue, Freight Service Expense and Contribution for LCVs	

Nationwide Scenario	XI-15
Table XI-9. Changes in Operational and Financial Indicators Under LCVs Nationwide Scenario	XI-15
Table XI-10. Lost Revenues, Freight Service Expense, and Contribution for Triples Nationwide Scenario	XI-17
Table XI-11. Changes in Rail Operational and Financial Indicators for the Triples Nationwide Scenario	XI-17
Table XI-12. Estimated Rail Rate Increase on All Traffic to Replace Lost Contribution and Restore ROI	XI-18
Table XII-1. Annual Transportation Cost Savings for Truck Shipments	XII-4

List of Figures

Figure I-1. Current Federal Truck Size and Weight Limits	I-1
Figure I-2. Public Policy Objectives Affected by Truck Size and Weight Regulations	I-2
Figure I-3. Major Truck Size and Weight Studies Since 1981	I-4
Figure I-4. National Freight Transportation Policy Statement	I-5
Figure II-1. Working Paper Topics	II-1
Figure II-2. Analytical Framework Overview	II-2
Figure II-3. Truck Size and Weight Analytical Process	II-3
Figure II-4. Illustrative Vehicle Configurations	II-5
Figure II-5. National Network for STAA Vehicles	II-8
Figure II-6. National Highway System Map	II-8
Figure II-7. Analytical Network for Long Double-Trailer Combinations	II-9
Figure II-8. Analytical Network for Triple-Trailer Combinations	II-9
Figure II-9. Base Case Federal Truck Size and Weight Limits	II-10
Figure II-10. Tridem Axle Definition	II-11
Figure II-11. Weigh-Out versus Cube-Out Freight	II-12
Figure II-12. Factors Affecting Pavement Life	II-14
Figure II-13. Factors Contributing to Truck Crashes	II-16
Figure II-14. Vehicle Stability and Control Considerations	II-16
Figure III-1. Illustrative Truck Size and Weight Scenarios	III-1
Figure III-2. State Semitrailer Lengths on the NN	III-2
Figure III-3. Truck Size and Weight Analysis Regions	III-6
Figure III-4. Divisible and Non-divisible Load Permits	III-8
Figure III-5. Uniformity Scenario	III-9
Figure III-6. Comparative Fleet Profiles -- Canada, United States, and Mexico	III-12
Figure III-7. Non-divisible Load Permits for International Containers	III-14
Figure III-8. North American Trade Scenarios	III-16
Figure III-9. The ISTEA Longer Combination Vehicle Freeze	III-17
Figure III-10. Comparison of Longer Combination Vehicles With Conventional Trucks	III-18

Figure III-11. States Allowing Various Longer Combination Vehicles	III-19
Figure III-12. Special Permits for Longer Combination Vehicles	III-20
Figure III-13. Longer Combination Vehicles Nationwide Scenario	III-21
Figure III-14. The Symms Amendment	III-25
Figure III-15. H.R. 551 Scenario	III-26
Figure III-16. Triples Nationwide Scenario	III-27
Figure IV-1. Analysis of Scenario Vehicle Miles of Travel and Car Miles	IV-2
Figure IV-2. The Surface Transportation Board’s Waybill Sample	IV-3
Figure IV-3. Five-Axle Tractor Semitrailers	IV-4
Figure IV-4. Five-Axle Tractor Semitrailer Diversion Options	IV-5
Figure IV-5. Rail Intermodal Equipment	IV-6
Figure IV-6. Trailer-on-Flatcar/Container-on-Flatcar Operations	IV-7
Figure IV-7. Rail Carload Equipment	IV-7
Figure IV-8. Intermodal Transportation and Inventory Cost Model	IV-8
Figure IV-9. Truck and Rail Mode Choice	IV-10
Figure IV-10. Intermodal Transportation and Inventory Cost Model Development	IV-11
Figure IV-11. Diversion of Freight Transported in Short Double-Trailer Combinations ...	IV-12
Figure IV-12. ITIC Model Calibration	IV-13
Figure IV-13. Weight Distribution Example - Base Case and Uniformity Scenario for Four-Axle Single Unit Truck	IV-15
Figure IV-14. Use of the Intermodal Transportation and Inventory Cost Model in Analyzing the Uniformity Scenario	IV-16
Figure IV-15. Uniformity Scenario - Likely Truck Configuration Impacts	IV-17
Figure IV-16. Impacts of Uniformity Scenario on Multitrailer Combination VMT	IV-18
Figure IV-17. Impacts of Uniformity Scenario on VMT by Single Unit Trucks, Truck-Trailers, and Tractor-Semitrailers	IV-18
Figure IV-18. Total VMT, Base Case Vs. Uniformity Scenario	IV-19
Figure IV-19. Likely Truck Configuration Impacts for North American Trade Scenario	IV-20
Figure IV-20. Impact of North American Trade Scenario (44,000 lb. Tridem Axle) on VMT By Different Vehicles	IV-20
Figure IV-21. Impact of North American Trade Scenario (44,000 pound Tridem Axle) on Total Heavy-Truck VMT	IV-21
Figure IV-22. Impacts of North American Trade Scenario (51,000 pound Tridem Axle) On VMT by Different Vehicles	IV-22
Figure IV-23. VMT for Base Case and North American Trade Scenario (51,000 pound Tridem Axle)	IV-22
Figure IV-24. Rail Intermodal Input Data	IV-23
Figure IV-25. Likely Truck Configuration Impacts of the LCV Nationwide Scenario	IV-25
Figure IV-26. Impacts of LCV Nationwide Scenario on VMT by Different Vehicles	IV-26
Figure IV-27. Total VMT for Base Case and LCV Nationwide Scenario	IV-26
Figure IV-28. Operating Restrictions	IV-28
Figure IV-29. Impact of Long-Doubles Network and Access Provisions	IV-29
Figure IV-30. Likely Truck Configuration Impacts, H.R. 551 Scenario	IV-30

Figure IV-31. Impacts of H.R. 551 Scenario on VMT by Different Vehicles	IV-30
Figure IV-32. Total VMT - Base Case and H.R. 551 Scenario	IV-31
Figure IV-33. Use of the Intermodal Transportation and Inventory Cost Model to Analyze the H.R. 551 Scenario	IV-31
Figure IV-34. Likely Truck Configuration Impacts of Triples Nationwide Scenario	IV-32
Figure IV-35. Impact of Triples Nationwide Scenario on VMT by Different Vehicles	IV-33
Figure IV-36. Impacts of Triples Nationwide Scenario on Total Truck VMT	IV-34
Figure V-1. Pavement Fatigue	V-2
Figure V-2. Impact of Axle Load on Fatigue in Flexible and Rigid Pavements	V-3
Figure V-3. The AASHO Road Test	V-4
Figure V-4. Flexible Versus Rigid Pavements	V-5
Figure V-5. Use of Spread-Tandem Versus Tridem Axles	V-10
Figure V-6. Tridem Axle Infrastructure Impacts	V-12
Figure VI-1. Structurally Deficient versus Functionally Obsolete Bridges	VI-1
Figure VI-2. Simple and Continuous Span Bridges	VI-2
Figure VI-3. Moments	VI-2
Figure VI-4. Interaction of Bridge Span Length and Spacing of Truck Axle Groups	VI-3
Figure VI-5. H-15 and HS-20 Bridge Loadings	VI-5
Figure VI-6. Relationship of Overstress Criteria to Design Stress and Bridge Ratings	VI-6
Figure VI-7. National Bridge Inventory	VI-8
Figure VII-1. Kingpin Setting	VII-1
Figure VII-2. Low Speed Offtracking	VII-2
Figure VII-3. High-Speed Offtracking	VII-2
Figure VII-4. Basic Configurations Used in Roadway Geometry Analysis	VII-4
Figure VII-5. Staging Areas	VII-4
Figure VII-6. Swept Path	VII-5
Figure VII-7. Regions Used for Assessing Geometric Impacts	VII-7
Figure VII-8. Staging Area	VII-10
Figure VIII-1. Efforts to Establish Longer Combination Vehicle Crash Rates	VIII-2
Figure VIII-2. Fatal Crash Rates by Vehicle Class	VIII-3
Figure VIII-3. Fatal Crash Rates on Different Highway Classes	VIII-4
Figure VIII-4. Travel on Different Highway Classes by Single and Multitrailer Combinations.	VIII-4
Figure VIII-5. Normalized Fatal Crash Rates	VIII-5
Figure VIII-6. Trucks Involved in Fatal Crashes on Interstate Highways – 1994	VIII-6
Figure VIII-7. Trucks Involved in Fatal Crashes on Non-Interstate Highway – 1994	VIII-7
Figure VIII-8. Trucks Involved in Fatal Crashes on All Roadways – 1994	VIII-7
Figure VIII-9. Standard Evasive Maneuver	VIII-9
Figure VIII-10. Controlling Vehicle Instability	VIII-10
Figure VIII.11. Comparison of Stability and Control Measures for Scenario Vehicles Relative to Five-Axle Tractor Semitrailer	VIII-12
Figure IX-1. Highway Performance Monitoring System	IX-5
Figure X-1. Federal Highway Administration Highway Traffic Noise Prediction Model	X-4

Figure XI-1. What is a Decreasing Cost Industry?	XI-1
Figure XI-2. The Class I Railroad Industry	XI-2
Figure XI-3. Restructuring of the Railroad Industry	XI-2
Figure XI-4. Integrated Financial Model	XI-5
Figure XI-5. Rail Revenues	XI-5
Figure XI-6. Focus Railroads	XI-8
Figure XII-1. Transportation Costs and Changes in Truck Sizes and Weights	XII-1
Figure XII-2. Inventory Costs and Changes in Truck Sizes and Weights	XII-2