

DRAFT---DO NOT QUOTE OR CITE

TABLE 1. ARCHITECTURAL COATING VOLATILE ORGANIC COMPOUND CONTENT LEVELS

Unless otherwise specified, units are in grams of VOC per liter of coating thinned to the manufacturer's maximum recommendation excluding the volume of any water, exempt compounds, or colorant added to tint bases.

Coating category	Effective April 1, 1997
Antenna coatings	530
Anti-fouling coatings	400
Anti-graffiti coatings	600
Bituminous coatings and mastics	500
Bond breakers	600
Chalkboard resurfacers	450
Concrete curing compounds	350
Concrete protective coatings	400
Dry fog coatings	400
Extreme high durability coatings	800
Fire-retardant/resistive coatings:	
Clear	850
Opaque	450
Flat coatings:	
Exterior	250
Interior	250
Floor coatings	400
Flow coatings	650
Form release compounds	450
Graphic arts coatings (sign paints)	500
Heat reactive coatings	420
High temperature coatings	650
Impacted immersion coatings	780
Industrial maintenance coatings	450
Lacquers (including lacquer sanding sealers)	680
Magnesium cement coatings	600

DRAFT---DO NOT QUOTE OR CITE

Coating category	Effective April 1, 1997
Mastic texture coatings	300
Metallic pigmented coatings	500
Multi-colored coatings	580
Nonferrous ornamental metal lacquers and surface protectants	870
Nonflat coatings:	
Exterior	380
Interior	380
Nuclear coatings	420
Pretreatment wash primers	780
Primers and undercoaters	350
Quick-dry coatings:	
Enamels	450
Primers, sealers, and undercoaters	450
Repair and maintenance thermoplastic coatings	650
Roof coatings	250
Rust preventative coatings	400
Sanding sealers (other than lacquer sanding sealers)	550
Sealers (including interior clear wood sealers)	400
Shellacs:	
Clear	650
Opaque	550
Stains:	
Clear and semi transparent	550
Opaque	350
Low solids	120 ^a
Swimming pool coatings	600
Thermoplastic rubber coatings and mastics	550
Traffic marking coatings	150
Varnishes	450

DRAFT---DO NOT QUOTE OR CITE

TABLE 1. ARCHITECTURAL COATING VOLATILE ORGANIC
COMPOUND CONTENT LEVELS (Concluded)

Coating category	Effective April 1, 1997
Waterproofing sealers and treatments:	
Clear	600
Opaque	400
Wood preservatives:	
Below ground wood preservatives	550
Clear and semi transparent	550
Opaque	350
Low solids	120 ^a

^aUnits are grams of VOC per liter of coating, including water and exempt compounds, thinned to the maximum thinning recommended by the manufacturer.